

Object :  
Installation :  
Project number :  
Date :



## 1 Luminaire data

### 1.1 Ansell Lighting, Galaxy CCT LED Downlight (WW) (AGALED/1/CCT)

#### 1.1.1 Data sheet

Manufacturer: Ansell Lighting

AGALED/1/CCT

Galaxy CCT LED Downlight (WW)


#### Luminaire data

Luminaire efficiency : 80.2%  
Luminaire efficacy : 98.91 lm/W  
Classification : A50 ↓99.9% ↑0.1%  
CIE Flux Codes : 62 87 98 100 80  
UGR 4H 8H : 21.8 / 21.3  
Power : 15 W  
Luminous flux : 1483.7 lm

#### Equipped with

Quantity : 1  
Designation :  
  
Colour :  
Luminous flux : 1850 lm

Dimensions : Ø226 mm x 5 mm




Object :  
Installation :  
Project number :  
Date :



## 1.1 Ansell Lighting, Galaxy CCT LED Downlight (WW) (AGALED/1/CCT)

### 1.1.2 LDC



Manufacturer : Ansell Lighting  
Order number : AGALED/1/CCT  
Luminaire name : Galaxy CCT LED Downlight (WW)  
Equipment : 1 x 3030-4P3SX3+5630-8PCS 15 W  
Dimensions : D 226 mm x H 5 mm  
File name : rlx\_20170831082359.ldt

Efficiency factor : 80.2%  
Luminaire efficacy : 98.91 lm/W (A50)  
Light distribution  
Beam Angle : 38.1° C0  
39.9° C90  
38.8° C180  
36.6° C270