

Object :
Installation :
Project number :
Date :



1 Luminaire data

1.1 Ansell Lighting, Galaxy CCT LED Downlight (CW) (AGALED/1/CCT)

1.1.1 Data sheet

Manufacturer: Ansell Lighting

AGALED/1/CCT

Galaxy CCT LED Downlight (CW)

Luminaire data


Luminaire efficiency : 82.2%
Luminaire efficacy : 103.85 lm/W
Classification : A50 ↓99.9% ↑0.1%
CIE Flux Codes : 62 87 98 100 82
UGR 4H 8H : 22.3 / 21.3
Power : 15 W
Luminous flux : 1557.7 lm

Equipped with

Quantity : 1
Designation :

Colour :
Luminous flux : 1895 lm

Dimensions : Ø226 mm x 5 mm




Object :
 Installation :
 Project number :
 Date :



1.1 Ansell Lighting, Galaxy CCT LED Downlight (CW) (AGALED/1/CCT)

1.1.2 LDC



Manufacturer	: Ansell Lighting	Efficiency factor	: 82.2%
Order number	: AGALED/1/CCT	Luminaire efficacy	: 103.85 lm/W (A50)
Luminaire name	: Galaxy CCT LED Downlight (CW)	Light distribution	
Equipment	: 1 x 3030-4P3SX3+5630-8PCS 15 W	Beam Angle	: 40.6° C0
Dimensions	: D 226 mm x H 5 mm		: 40.7° C90
File name	: rlx_20170831082401.ldt		: 37.8° C180
			: 37.9° C270