

Object :
Installation :
Project number :
Date :

1 Luminaire data

1.1 Ansell Lighting, Neptune LED CCT Troffer (6000K) (ANEPLED)

1.1.1 Data sheet

Manufacturer: Ansell Lighting

ANEPLED Neptune LED CCT Troffer (6000K)


Luminaire data

Luminaire efficiency : 100%
Luminaire efficacy : 101.81 lm/W
Classification : A40 ↓99.9% ↑0.1%
CIE Flux Codes : 44 75 95 100 100
UGR 4H 8H : 19.9 / 23.0
Power : 37 W
Luminous flux : 3767 lm

Equipped with


Quantity : 1
Designation :
Colour :
Luminous flux : 3767 lm

Dimensions : 600 mm x 600 mm x 1 mm



1.1 Ansell Lighting, Neptune LED CCT Troffer (6000K) (ANEPLED)

1.1.2 LDC



Manufacturer	: Ansell Lighting	Efficiency factor	: 100%
Order number	: ANEPLED	Luminaire efficacy	: 101.81 lm/W (A40)
Luminaire name	: Neptune LED CCT Troffer (6000K)	Light distribution	
Equipment	: 1 x 37 W / 3767 lm	Beam Angle	: 54.0° C0
Dimensions	: L 600 mm x W 600 mm x H 1 mm		66.5° C90
File name	: rlx_20180910071226.ltd		55.1° C180
			67.8° C270