

1 Luminaire data

1.1 Ansell Lighting, Neptune LED CC Troffer (3000K) (ANEPLED)

1.1.1 Data sheet

Manufacturer: Ansell Lighting

ANEPLED Neptune LED CC Troffer (3000K)


Luminaire data

Luminaire efficiency : 100%
Luminaire efficacy : 99 lm/W
Classification : A40 ↓99.9% ↑0.1%
CIE Flux Codes : 44 75 95 100 100
UGR 4H 8H : 19.7 / 22.9
Power : 36 W
Luminous flux : 3564 lm

Dimensions : 600 mm x 600 mm x 1 mm

Equipped with


Quantity : 1
Designation :
Colour :
Luminous flux : 3564 lm



Object :
Installation :
Project number :
Date :

1.1 Ansell Lighting, Neptune LED CC Troffer (3000K) (ANEPLED)

1.1.2 LDC



Manufacturer : Ansell Lighting
Order number : ANEPLED
Luminaire name : Neptune LED CC Troffer (3000K)
Equipment : 1 x 36 W / 3564 lm
Dimensions : L 600 mm x W 600 mm x H 1 mm
File name : rlx_20180910071132.ltd

Efficiency factor : 100%
Luminaire efficacy : 99 lm/W (A40)
Light distribution
Beam Angle : 54.0° C0
66.2° C90
55.0° C180
67.9° C270