

250A type B KQ Loadcenter incoming devices



SE250SW3L

Reference number	Device type	Current rating	Number of poles	Standard approval	Cable capacity mm ²
SE250L4P	Terminal block	250A	4	–	185
SE160SW3L	Switch disconnector	160A	3+N	BS EN 60947-3	95
SE200SW3L	Switch disconnector	200A	3+N	BS EN 60947-3	185
SE250SW3L	Switch disconnector	250A	3+N	BS EN 60947-3	185
SE160SW4	Switch disconnector	160A	4	BS EN 60947-3	95
SE200SW4	Switch disconnector	200A	4	BS EN 60947-3	185
SE250SW4	Switch disconnector	250A	4	BS EN 60947-3	185
SE100MCCB3L	MCCB	100A	3+N	BS EN 60947-2	95
SE160MCCB3L	MCCB	160A	3+N	BS EN 60947-2	95
SE200MCCB3L	MCCB	200A	3+N	BS EN 60947-2	185
SE250MCCB3L	MCCB	250A	3+N	BS EN 60947-2	185
SE160RCD	RCCB 160A	Adjustable 30mA - 10A	4	BS EN 61008	95

Note Supplied with 400mm extension box

KQ Loadcenter - three phase B type distribution boards



SE250MET

Reference number	Description
SE250MET	MID 3 Phase kWh kit Modbus communications and Pulsed output (Includes A9MEM3255)

Incomers for 250A split metered boards



SE160SW4SM

Reference number	Device type	Current rating	Number of poles	Standard approval	Cable capacity mm ²
SE160SW4SM	Switch disconnector	160A	4	BS EN 60947-3	95
SE200SW4SM	Switch disconnector	200A	4	BS EN 60947-3	185
SE250SW4SM	Switch disconnector	250A	4	BS EN 60947-3	185
SE160MCCB3LSM	MCCB	160A	4	BS EN 60947-2	95
SE200MCCB3LSM	MCCB	200A	4	BS EN 60947-2	185
SE250MCCB3LSM	MCCB	250A	4	BS EN 60947-2	185