

Panelboards - I-Line MCCB panelboards Size 2 630A



Size 2 630A panelboards

- Degree of protection IP3X
- Door lock fitted as standard
- Ample cabling space
- I-Line busbar
- Removable neutral link
- Hinged lift off cable way covers
- MCCB separation to form 3b Type 2 BS EN 61439-1
- Fully rated earth and neutral bars
- Removable top and bottom gland plates
- Simple ordering
- Maximum outgoing 250A
- Busbar rating 50ka for 1s

Step 1 Select panelboard required

Description	Modules	Reference number 630A
6 triple pole outgoing ways	9+9	MP63062
10 triple pole outgoing ways	15+15	MP630102
14 triple pole outgoing ways	21+21	MP630142
18 triple pole outgoing ways	27+27	MP630182

Step 2 Select incoming device

	Reference number
250A 36kA triple pole MCCB	SLA3250
400A 36kA triple pole MCCB	SLA3400
400A automatic switch disconnect (isolator)	SLA3000M
600A 50kA triple pole MCCB	PJA36060CU31A
600A automatic switch disconnect (isolator)	PJA36000S60
630A main lugs kit	ML630

Step 3 Select outgoing devices

Single and double pole MCCB 's are phase dedicated.
To obtain correct reference add suffix as below example:
40A SP MCCB to fit L3 will be SFA1040CC



MCCB								
16-100A 25kA	Single Pole (1 Mod)			Double Pole (2 Mod)				
		L1	L2	L3		L1/L2	L2/L3	L1/L3
		Suffix				Suffix		
16A	SFA1016	A	B	C	SFA2016	AB	BC	AC
20A	SFA1020				SFA2020			
32A	SFA1032				SFA2032			
40A	SFA1040				SFA2040			
50A	SFA1050				SFA2050			
63A	SFA1063				SFA2063			
80A	SFA1080				SFA2080			
100A	SFA1100				SFA2100			