



400A NH VM160 PANELBOARD



NHVM34012



NHVL3400CK + NHVL3400MCCB

400A PANELBOARD

Outgoing Ways	H	W	D	List No
6 way	1132mm	700mm	198mm	NHVM34006
12 way	1361mm	700mm	198mm	NHVM34012
18 way	1591mm	700mm	198mm	NHVM34018

- 400A rated
- Type tested & ASTA certified to IEC 61439-2; Ed 2 2011-08
- 35kA for 1s Short Circuit Withstand Strength
- 3b Type 2 Form of Separation
- IP3X (door closed)

400A PANELBOARD INCOMERS

Description	List No
400A TP Switch Disconnecter	NHVL3400SW
400A 4P Switch Disconnecter	NHVL4400SW
400A TP MCCB	NHVL3400MCCB
400A 4P MCCB	NHVL4400MCCB
400A Direct Connection Coppers	NHVL4400DC
Incoming Device Interconnections TP*	NHVL3400CK
Incoming Device Interconnections 4P*	NHVL4400CK

* Inter connections are necessary when selecting a switch disconnecter or MCCB incoming device

- Max cable lug connection/busbar 32mm wide

MCCBs:

- Electronic Trip Unit LI for System Protection

Switch Disconnectors:

- Fixed Short Circuit Release

INCOMER TERMINAL EXTENSIONS

TP Incomers	List No
Front connecting bars (for increased pole spacing, max 32mmx10mm bar)	NHVL9400-4ED30
Box Terminals 50...300mm ²	NHVL9400-4TC30
Circular Conductor Terminals 50...300mm ²	NHVL9400-4TD30
Multiple feed-in Terminal 2 x 70...300mm ²	NHVL9460-4TF30
Screw Connection Terminals M8	NHVL9400-4TA30

4P Incomers	List No
Front connecting bars (for increased pole spacing, max 32mmx10mm bar)	NHVL9400-4ED40
Box Terminals 50...300mm ²	NHVL9400-4TC40
Circular Conductor Terminals 50...300mm ²	NHVL9400-4TD40
Multiple feed-in Terminal 2 x 70...300mm ²	NHVL9460-4TF40
Screw Connection Terminals M8	NHVL9400-4TA40