

FUSESTAR HOUSED SWITCH DISCONNECTOR

	Sheet Steel Enclosure						
RATING IN AMPS	20A	32A	40A	63A	63A	100A	125A
Rated Insulation Voltage U_i (V)	800	800	800	800	800	800	800
Dielectric Strength (kV) 50 Hz 1min	3	3	3	3	3	3	3
Shock Resistance U_{imp} (kV)	8	8	8	8	8	8	8
OPERATIONAL CURRENT I_e (A)							
415 V AC - AC21A / AC21B	20	32	40	63	80	100	125
AC22A / AC22B	20	32	40	63	80	100	125
AC23A / AC23B	20	32	40	63	80	80	80
500 V AC - AC21A / AC21B	20	32	40	63	80	100	125
AC22A / AC22B	20	32	40	63	80	100	125
AC23A / AC23B	20	32	40	40	63	63	63
690 V AC - AC20A / AC20B	20	32	40	63	80	100	125
AC21A / AC21B	20	32	40	63	80	100	125
AC22A / AC22B	20	32	40	63	80	100	100
AC23A / AC23B	20	25	25	25	50	50	50
MOTOR POWER (kW) AC 23							
415 V AC	7.5	11	11	15	18.5	37	40
500 V AC	7.5	11	15	18.5	22	37	37
690 V AC	11	11	18.5	18.5	25	30	30
FUSE TYPES TO BS88							
OVERLOAD CAPACITY							
Fuse rating gG	20	32	40	63/40	63	100	125
Short circuit current with fuses (kA Rms)	50	50	50	20/50	50	20	15
Asymmetric short time rating current (kA peak)	6	6	6	9	9	9	9
Admissible short time current 1 s. (kA Rms)	1.26	1.26	1.26	1.5	1.5	1.5	1.5
MAKING & BREAKING CHARACTERISTICS							
Breaking capacity (A Rms) 415 V AC 23 A	160	256	320	504	504	640	640
Making capacity (A Rms) 415 V AC 23 A	200	320	400	630	630	800	800
WITHSTAND							
Mechanical (number of operations) x 1000	100	100	100	100	30	30	30
Electrical (number of operations at 415V AC 23A) x 1000	3	3	3	3	1.5	1.5	1.5
CONNECTION							
Maximum Cu cable section (mm ²) lth	16	16	16	16	50	50	50
using stranded cable (mm ²)							
WEIGHT (kg)							
3 pole	2.00	2.00	2.00	2.00	2.50	2.50	2.50
4 pole	2.00	2.00	2.00	2.00	2.50	2.50	2.50
BOX SIZE	1	1	1	1	2	2	2