# **DECORATIVE 3A ENERGY SAVING CARD SWITCH**


# **DIMENSIONS (mm)**

## **METAL PLATE**

Back Box Size:25mm (Recommended)Back Box Ref:SB655 (Flush Metal Box 25mm)Back Box Ref:SB619 (Dry Lining Box 35mm)Plate Material:Mild Steel, 8.5mm depth

Base Material: Polycarbonate Interior Material: Polycarbonate

Processes: Polished / brushed plate, Electrophoresis, Stoved




#### PLATINUM LOW PROFILE METAL PLATE

Back Box Size:35mm (Recommended)Back Box Ref:SB615 (Flush Metal Box 35mm)Back Box Ref:SB619 (Dry Lining Box 35mm)Plate Material:Mild Steel, 3.1mm depth

Base Material: Polycarbonate Interior Material: Polycarbonate

Processes: Polished / brushed plate, paint or Electrophoretically

Laquered, Stoved



### A POINT OF TESTING

When installations incorporating electronic devices of the semi conductor type are being tested, care must always be taken to ensure that they are not subjected to the output voltage of the insulation tester. However, dimmer switches complying with BS 5518 will not be damaged by the application of a normal 500V insulation resistance test. In all other cases where electronic items are fitted, they should be disconnected whilst the insulation of the installation is being tested. A notice, drawing to the attention to the fact that electronic devices are incorporated in the installation, should always be affixed at the intake position. This also applies to any neon indicators fitted.