DECORATIVE SHAVER SUPPLY UNIT


DIMENSIONS (mm)


METAL PLATE

Back Box Size: 47mm (Recommended)
Back Box Ref: SB628 (Flush Metal Box 47mm)
Back Box Ref: SB631 (Dry Lining Box 47mm)
Plate Material: Mild Steel, 8.5mm depth

Interior Material: Polycarbonate

Processes: Polished / brushed plate, Electrophoresis, Stoved







PLATINUM LOW PROFILE WHITE MOULDED PLATE

Back Box Size:55mm (Recommended)Back Box Ref:SB628 (Flush Metal Box 47mm)Back Box Ref:SB631 (Dry Lining Box 47mm)

Plate Material: Polycarbonate, 4.6mm deep detachable plate

Interior Material: Polycarbonate Processes: Moulded






PLATINUM LOW PROFILE METAL PLATE


Back Box Size: 55mm (Recommended)
Back Box Ref: SB628 (Flush Metal Box 47mm)
Back Box Ref: SB631 (Dry Lining Box 47mm)
Plate Material: Mild Steel, 1.5mm depth

Interior Material: Polycarbonate

Processes: Polished / brushed plate, Paint or Electrophoretically

Lacquered, Stoved






PLATINUM FLAT METAL PLATE


Back Box Size: 55mm (Recommended)
Back Box Ref: SB628 (Flush Metal Box 47mm)
Back Box Ref: SB631 (Dry Lining Box 47mm)
Plate Material: Mild Steel, 1.5mm depth

Interior Material: Polycarbonate

Processes: Polished / brushed plate, Electrophoretically

Lacquered, Stoved





A POINT OF TESTING

When installations incorporating electronic devices of the semi conductor type are being tested, care must always be taken to ensure that they are not subjected to the output voltage of the insulation tester. However, dimmer switches complying with BS 5518 will not be damaged by the application of a normal 500V insulation resistance test. In all other cases where electronic items are fitted, they should be disconnected whilst the insulation of the installation is being tested. A notice, drawing to the attention to the fact that electronic devices are incorporated in the installation, should always be affixed at the intake position. This also applies to any neon indicators fitted.