CR1004

2 GANG ARCHITRAVE BLANK PLATE





(5)

CONSTRUCTION

Product Category Wiring Accessory **Product Group** Ancillary Item **Product Type** Blank Plate Rectangular Plate Shape Material Urea Formaldehyde Finish Moulded **Mounting Type** Flush/Surface

POWER

Current Not Applicable **Current Type** Not Applicable Not Applicable Frequency Input Voltage Not Applicable **Switched Poles** Not Applicable **Number of Rocker Switches** Number of Ways Not Applicable **Fuse Rating** Not Applicable

AESTHETICS

Plate Gang / Module Size 2 Gang Architrave Plate Colour White **Rocker Colour** Not Applicable Light Reflectance Value (LRV) Printing Text/Type Not Applicable Status Indicator Ν **Switched Outlets** Ν

Part M Compliance **Anti Microbial Properties**

Key Features & Benefits Curved Slimline Plate Front Fixed & Screw Retained

TERMINAL

L & N Terminal Capacity as per BS Standard Not Applicable Earth Terminal Capacity as per BS Standard Not Applicable **Number of Earth Terminals** Not Applicable **Cable Strip Length Screwdriver Type Required** Slotted Type Torque requirement as per BS Standard L&N Not Applicable Torque requirement as per BS Standard Earth Not Applicable

LOCATION

Max Ambient Operating Temp as per BS Req. Not Applicable Min Ambient Operating Temp as per BS Req. Max Altitude as per BS Requirement Not Applicable 2000m **IP Rating** IP2X

DIMENSIONAL / FIXING

Height 146.5mm Width 32.5mm Depth Overall (Inc Rocker) 9mm **Depth Interior only** Not Applicable Gross Weight 0.032kg Minimum Back Box Depth Suggested Back Box Depth Not Applicable Not Applicable **Fixing Centres** 120.6mm Minimum Access Top 100cm Minimum Access Bottom 100cm **Minimum Access Left** 100cm **Minimum Access Right** 100cm **Minimum Access Front** 100cm **Minimum Access Rear** 100cm Flush Mounting Metal Box 9258 (28mm) Not Applicable Flush Mounting Dry Lining Box **Surface Mounting Box** 4006 (20mm)

STANDARDS

British Standard/s BS 5733 Other Markings/Standards CF

PACKAGING

Inner Carton Qty 20 **Customer MOQ** 20

SUSTAINABILITY

URL to technology list https://www.crabtreecommercial.co.uk/



Fax: +44 (0) 1543 000000 Email: crabtree.technical@electrium.co.uk

www.electrium.co.uk

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this publication, specifications and performance data are constantly changing. Latest details can be obtained from Crabtree



