CR1257/CE/BL

13A 2G UNSWITCHED SOCKET CLEAN EARTH ALL BLUE





CONSTRUCTION

Product CategoryWiring AccessoryProduct GroupPower & ControlProduct TypeSocket Outlet Typ

Socket Outlet Type G (Standard UK 3 Pin)

Shape Rectangular Plate
Material Urea Formaldehyde
Finish Moulded
Mounting Type Flush/Surface

POWER

 Current
 13 Amps

 Current Type
 AC

 Frequency
 50Hz

 Input Voltage
 250V

Switched Poles Not Applicable
Number of Rocker Switches 0

Number of Ways Not Applicable
Fuse Rating Not Applicable

AESTHETICS

 Plate Gang / Module Size
 2 Gang

 Plate Colour
 Blue

 Rocker Colour
 Not Applicable

 Light Reflectance Value (LRV)
 20

Printing Text/Type Medical Equipment Only, Laser Printed

Safety Shutter System

Status Indicator N
Switched Outlets N
Part M Compliance Y
Anti Microbial Properties Y

Key Features & Benefits

Curved Slimline Plate
All Upward Facing Terminals
Full Contact Cable Clamp

TERMINAL

L & N Terminal Capacity as per BS Standard
Earth Terminal Capacity as per BS Standard
3 x 2.5mm², 2 x 4.0mm²
3 x 1.5mm², 3 x 2.5mm², 2 x 4.0mm²

 Number of Earth Terminals
 4

 Cable Strip Length
 12mm

 Screwdriver Type Required
 Slotted Type

Torque requirement as per BS Standard L&N

Torque requirement as per BS Standard Earth

1.2Nm

LOCATION

Max Ambient Operating Temp as per BS Req. +40°C
Min Ambient Operating Temp as per BS Req. -5°C
Max Altitude as per BS Requirement | 2000m
IP Rating | IP2X

DIMENSIONAL / FIXING

Height 86mm Width 146mm **Depth Overall** 24.5mm Depth Interior only 16mm **Gross Weight** 0.164kg Minimum Back Box Depth 25mm Suggested Back Box Depth 25mm Fixing Centres 120.6mm Minimum Access Top 100cm Minimum Access Bottom 100cm **Minimum Access Left** 100cm **Minimum Access Right** 100cm Minimum Access Front 100cm Minimum Access Rear 100cm

Flush Mounting Metal Box SB665 (25mm) or CR2203/BG (40mm)

Flush Mounting Dry Lining Box SB629 (35mm)
Surface Mounting Box 9048 (29mm)

STANDARDS


British Standard/s BS 1363-2 Other Markings/Standards CE


PACKAGING

Inner Carton Qty5Customer MOQ5

SUSTAINABILITY

URL to technology list https://www.crabtreecommercial.co.uk/





86

Electrium Sales Limited
A Siemens Company
Tel: +44 (0) 1543 438310
Fax: +44 (0) 1543 000000

Fax: +44 (0) 1543 000000 Email: crabtree.technical@electrium.co.uk

www.electrium.co.uk

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this publication, specifications and performance data are constantly changing.

Latest details can be obtained from Crabtree.



