## CR2162/G

**10A 2 WAY RETRACTIVE GRID SWITCH** WITH GREY ROCKER





## **CONSTRUCTION**

**Product Category** Wiring Accessory **Product Group** Lighting Control **Product Type** Grid Switch Rectangle Shape Urea Formaldehyde Material Finish Moulded

**Mounting Type** Flush/Surface Grid System

**POWER** 

Current 10 Amps **Current Type**  $\Delta C$ 50Hz Frequency Input Voltage 250V **Switched Poles** Single Pole **Number of Rocker Switches** Number of Ways

Not Applicable **Fuse Rating** 

**AESTHETICS** 

Plate Gang / Module Size 1 Grid Module Plate Colour Green **Rocker Colour** Grey Light Reflectance Value (LRV) Printing Text/Type Not Applicable Status Indicator

**Switched Outlets** Ν Part M Compliance Anti Microbial Properties

**Key Features & Benefits** Curved Slimline Profile All Upward Facing Terminals Full Contact Cable Clamp

**TERMINAL** 

L & N Terminal Capacity as per BS Standard 4 x 1.0mm<sup>2</sup>, 3 x 1.5mm<sup>2</sup>, 1 x 2.5mm<sup>2</sup> **Earth Terminal Capacity as per BS Standard** Not Applicable **Number of Earth Terminals** Cable Strip Length 10mm Slotted Type

Front Fixed & Screw Retained

Screwdriver Type Required Torque requirement as per BS Standard L&N 0.5Nm Torque requirement as per BS Standard Earth 0.5Nm

**LOCATION** 

Max Ambient Operating Temp as per BS Req. Occasionally reaching +35°C Min Ambient Operating Temp as per BS Req. Not exceeding +25°C Max Altitude as per BS Requirement **IP Rating** IP2X (Full Instinct Grid Assembly)

**DIMENSIONAL / FIXING** 

Height 55mm 25mm Depth Overall (Inc Rocker) 23mm **Depth Interior only** 16mm **Gross Weight** 0.014kg Minimum Back Box Depth 16mm Suggested Back Box Depth 16mm Fixing Centres Not Applicable Minimum Access Top 100cm **Minimum Access Bottom** 100cm **Minimum Access Left** 100cm Minimum Access Right 100cm Minimum Access Front 100cm **Minimum Access Rear** 100cm Not Applicable Flush Mounting Metal Box Not Applicable

Flush Mounting Dry Lining Box Surface Mounting Box Not Applicable

**STANDARDS** 

**British Standard/s** BS EN 60669-1 CE


Other Markings/Standards

**PACKAGING** 

**Inner Carton Qty** 6 **Customer MOQ** 6

**SUSTAINABILITY** URL to technology list

https://www.crabtreecommercial.co.uk/



**Electrium Sales Limited** A Siemens Company +44 (0) 1543 438310 Fax: +44 (0) 1543 000000 Email: crabtree.technical@electrium.co.uk

www.electrium.co.uk

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this publication, specifications and performance data are constantly changing. Latest details can be obtained from Crabtree



