CR2201/PBG

1 & 2 GANG SURFACE BOX WITHOUT KNOCKOUTS





CONSTRUCTION

Product CategoryWiring AccessoryProduct GroupPower & ControlProduct TypeGrid SystemShapeNot ApplicableMaterialMild SteelFinishNot ApplicableMounting TypeSurface

POWER

CurrentNot ApplicableCurrent TypeNot ApplicableFrequency50HzInput Voltage250VSwitched PolesNot ApplicableNumber of Rocker Switches0

Number of Ways Not Applicable
Fuse Rating Not Applicable

AESTHETICS

Plate Gang / Module Size 1 Gang
Plate Colour Birch Grey
Rocker Colour Not Applicable
Light Reflectance Value (LRV) 29
Printing Text/Type Not Applicable
Status Indicator N
Switched Outlets N

Switched Outlets N
Part M Compliance Y
Anti Microbial Properties N
Key Features & Benefits Coa

Key Features & BenefitsCoated in Low Smoke & Fume (LSF)
Powder Coat Finish as standard

Robust & Reliable

TERMINAL

L & N Terminal Capacity as per BS Standard
Earth Terminal Capacity as per BS Standard
Number of Earth Terminals
Cable Strip Length
Screwdriver Type Required
Torque requirement as per BS Standard L&N
Torque requirement as per BS Standard Earth
Not Applicable
Not Applicable
Not Applicable
Not Applicable

LOCATION

Max Ambient Operating Temp as per BS Req.Not ApplicableMin Ambient Operating Temp as per BS Req.Not ApplicableMax Altitude as per BS Requirement2000mIP RatingNot Applicable

DIMENSIONAL / FIXING

Height 85.6mm Width 85.6mm Depth 40mm Not Applicable **Depth Interior only** 0.174kg Gross Weight Minimum Back Box Depth Not Applicable Suggested Back Box Depth Not Applicable Fixing Centres 60.3mm Minimum Access Top 100cm Minimum Access Bottom 100cm Minimum Access Left 100cm **Minimum Access Right** 100cm **Minimum Access Front** 100cm Minimum Access Rear 100cm Flush Mounting Metal Box Not Applicable Flush Mounting Dry Lining Box Not Applicable

PACKAGING


Inner Carton Qty 10 Customer MOQ 10

SUSTAINABILITY

Surface Mounting Box

URL to technology list https://www.crabtreecommercial.co.uk/

Not Applicable



Electrium Sales Limited
A Siemens Company
Tel: +44 (0) 1543 438310
Fax: +44 (0) 1543 000000

Fax: +44 (0) 1543 000000 Email: crabtree.technical@electrium.co.uk

www.electrium.co.uk

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this publication, specifications and performance data are constantly changing.

Latest details can be obtained from Crabtree.



