CR2203/BG

3 & 4 GANG SURFACE BOX





CONSTRUCTION

Product Category Wiring Accessory **Product Group** Power & Control **Product Type** Grid System Not Applicable Shape Material Mild Steel Finish Not Applicable **Mounting Type** Surface

POWER

Current Not Applicable Not Applicable **Current Type** 50Hz Frequency Input Voltage 250V **Switched Poles** Not Applicable **Number of Rocker Switches** Number of Ways Not Applicable

AESTHETICS

Fuse Rating

Plate Gang / Module Size 2 Gang Plate Colour Birch Grev **Rocker Colour** Not Applicable Light Reflectance Value (LRV) Printing Text/Type Not Applicable Status Indicator Ν **Switched Outlets** Ν Part M Compliance **Anti Microbial Properties** Ν

Key Features & Benefits Coated in Low Smoke & Fume (LSF) Powder Coat Finish as standard

Robust & Reliable

Not Applicable

TERMINAL

L & N Terminal Capacity as per BS Standard Not Applicable Earth Terminal Capacity as per BS Standard Not Applicable **Number of Earth Terminals Cable Strip Length** Not Applicable Screwdriver Type Required Not Applicable Torque requirement as per BS Standard L&N Not Applicable Torque requirement as per BS Standard Earth Not Applicable

LOCATION

Max Ambient Operating Temp as per BS Req. Not Applicable Not Applicable Min Ambient Operating Temp as per BS Req. Max Altitude as per BS Requirement 2000m IP Rating Not Applicable

DIMENSIONAL / FIXING

Height 85.6mm Width 146mm Depth 40mm 0.260kg **Depth Interior only** Gross Weight Not Applicable Minimum Back Box Depth Not Applicable **Suggested Back Box Depth** Not Applicable Fixing Centres 120.6mm Minimum Access Top 100cm Minimum Access Bottom 100cm Minimum Access Left 100cm **Minimum Access Right** 100cm **Minimum Access Front** 100cm Minimum Access Rear 100cm Flush Mounting Metal Box Not Applicable Flush Mounting Dry Lining Box Not Applicable

PACKAGING


Inner Carton Qty 5 5 **Customer MOQ**

SUSTAINABILITY

Surface Mounting Box

URL to technology list https://www.crabtreecommercial.co.uk/

Not Applicable



Electrium Sales Limited A Siemens Company +44 (0) 1543 438310 Fax: +44 (0) 1543 000000 Email: crabtree.technical@electrium.co.uk

www.electrium.co.uk

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this publication, specifications and performance data are constantly changing. Latest details can be obtained from Crabtree



