# CR2209/PBG

WITHOUT KNOCKOUTS





# **CONSTRUCTION**

**Product Category** Wiring Accessory **Product Group** Power & Control **Product Type** Grid System Not Applicable Shape Material Mild Steel Finish Powder Coated **Mounting Type** Flush/Surface

## **POWER**

Current Not Applicable Not Applicable **Current Type** 50Hz Frequency Input Voltage 250V **Switched Poles** Not Applicable **Number of Rocker Switches** Number of Ways Not Applicable **Fuse Rating** Not Applicable

## **AESTHETICS**

Plate Gang / Module Size 12 Gang **Plate Colour** Birch Grey Not Applicable **Rocker Colour** Light Reflectance Value (LRV) Not Applicable Printing Text/Type Not Applicable Status Indicator Ν **Switched Outlets** Ν Part M Compliance **Anti Microbial Properties** Ν **Key Features & Benefits** Not Applicable

## **TERMINAL**

L & N Terminal Capacity as per BS Standard Not Applicable Earth Terminal Capacity as per BS Standard 4 x 1.0mm<sup>2</sup>, 3 x 1.5mm<sup>2</sup>, 1 x 2.5mm<sup>2</sup> Number of Earth Terminals Not Applicable **Cable Strip Length Screwdriver Type Required** Not Applicable Torque requirement as per BS Standard L&N Not Applicable Torque requirement as per BS Standard Earth 1.2Nm

# LOCATION

Max Ambient Operating Temp as per BS Req. Not Applicable Min Ambient Operating Temp as per BS Req. Not Applicable Max Altitude as per BS Requirement 2000m IP Rating Not Applicable

# **DIMENSIONAL / FIXING**

Height 128mm Width 128mm Depth Overall (Inc Rocker) 35mm **Depth Interior only** Not Applicable **Gross Weight** Not Applicable Minimum Back Box Depth Not Applicable Suggested Back Box Depth Not Applicable **Fixing Centres** Not Applicable **Minimum Access Top** 100cm Minimum Access Bottom 100cm Minimum Access Left 100cm Minimum Access Right 100cm **Minimum Access Front** 100cm **Minimum Access Rear** 100cm Flush Mounting Metal Box Not Applicable Flush Mounting Dry Lining Box Not Applicable **Surface Mounting Box** Not Applicable

## **STANDARDS**


**British Standard/s** Not Applicable Other Markings/Standards Not Applicable

## **PACKAGING**

Inner Carton Qty **Customer MOQ** 

# **SUSTAINABILITY**

URL to technology list https://www.crabtreecommercial.co.uk/



**Electrium Sales Limited** A Siemens Company +44 (0) 1543 438310 Fax: +44 (0) 1543 000000 Email: crabtree.technical@electrium.co.uk

www.electrium.co.uk

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this publication, specifications and performance data are constantly changing. Latest details can be obtained from Crabtree



