

CR2570/24BG

24 GANG GRID COVER PLATE METALCLAD



InstinctTM
WIRING ACCESSORIES

CONSTRUCTION

Product Category	Wiring Accessory
Product Group	Power & Control
Product Type	Grid System
Shape	Rectangular Plate
Material	Mild Steel
Finish	Powder Coated
Mounting Type	Flush/Surface

POWER

Current	Not Applicable
Current Type	Not Applicable
Frequency	Not Applicable
Input Voltage	Not Applicable
Switched Poles	Not Applicable
Number of Rocker Switches	0
Number of Ways	Not Applicable
Fuse Rating	Not Applicable

AESTHETICS

Plate Gang / Module Size	24 Gang
Plate Colour	Birch Grey
Rocker Colour	Not Applicable
Light Reflectance Value (LRV)	29
Printing Text/Type	Not Applicable
Status Indicator	N
Switched Outlets	N
Part M Compliance	Y
Anti Microbial Properties	N
Key Features & Benefits	Curved Slimline Plate Front Fixed & Screw Retained

TERMINAL

L & N Terminal Capacity as per BS Standard	Not Applicable
Earth Terminal Capacity as per BS Standard	Not Applicable
Number of Earth Terminals	0
Cable Strip Length	Not Applicable
Screwdriver Type Required	Slotted Type
Torque requirement as per BS Standard L&N	Not Applicable
Torque requirement as per BS Standard Earth	Not Applicable

LOCATION

Max Ambient Operating Temp as per BS Req.	Not Applicable
Min Ambient Operating Temp as per BS Req.	Not Applicable
Max Altitude as per BS Requirement	2000m
IP Rating	IP2X (Full Instinct Grid Assembly)

DIMENSIONAL / FIXING

Height	206.3mm
Width	266.6mm
Depth Overall (Inc Rocker)	9mm
Depth Interior only	Not Applicable
Gross Weight	0.386kg
Minimum Back Box Depth	Not Applicable
Suggested Back Box Depth	Not Applicable
Fixing Centres	192mm
Minimum Access Top	100cm
Minimum Access Bottom	100cm
Minimum Access Left	100cm
Minimum Access Right	100cm
Minimum Access Front	100cm
Minimum Access Rear	100cm
Flush Mounting Metal Box	CR2209/24BG (40mm with knockouts)
Flush Mounting Dry Lining Box	Not Applicable
Surface Mounting Box	CR2209/24BG (40mm with knockouts)

STANDARDS


British Standard/s	BS 5733
Other Markings/Standards	CE

PACKAGING

Inner Carton Qty	1
Customer MOQ	1

SUSTAINABILITY

URL to technology list	https://www.crabtreecommercial.co.uk/
------------------------	---



Electrium Sales Limited
A Siemens Company
Tel: +44 (0) 1543 438310
Fax: +44 (0) 1543 000000
Email: crabtree.technical@electrium.co.uk
www.electrium.co.uk

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this publication, specifications and performance data are constantly changing. Latest details can be obtained from Crabtree.



Crabtree