CR2572

2 GANG GRID COVER PLATE





CONSTRUCTION

Product CategoryWiring AccessoryProduct GroupPower & ControlProduct TypeGrid SystemShapeSquare PlateMaterialUrea FormaldehydeFinishMouldedMounting TypeFlush/Surface

POWER

CurrentNot ApplicableCurrent TypeNot ApplicableFrequencyNot ApplicableInput VoltageNot ApplicableSwitched PolesNot ApplicableNumber of Rocker Switches0Number of WaysNot ApplicableFuse RatingNot Applicable

AESTHETICS

 Plate Gang / Module Size
 2 Gang

 Plate Colour
 White

 Rocker Colour
 Not Applicable

 Light Reflectance Value (LRV)
 74

 Printing Text/Type
 Not Applicable

 Status Indicator
 N

 Switched Outlets
 N

Switched Outlets N
Part M Compliance Y
Anti Microbial Properties Y
Key Features & Benefits Curved

Cey Features & BenefitsCurved Slimline Plate
Front Fixed & Screw Retained

TERMINAL

L & N Terminal Capacity as per BS Standard
Earth Terminal Capacity as per BS Standard
Number of Earth Terminals
Cable Strip Length
Screwdriver Type Required
Torque requirement as per BS Standard L&N
Torque requirement as per BS Standard Earth
Not Applicable
Not Applicable
Not Applicable

LOCATION

Max Ambient Operating Temp as per BS Req.Not ApplicableMin Ambient Operating Temp as per BS Req.Not ApplicableMax Altitude as per BS Requirement2000mIP RatingIP2X (Full Instinct Grid Assembly)

DIMENSIONAL / FIXING

Height 86mm Width 86mm **Depth Overall** 9mm Not Applicable **Depth Interior only** Gross Weight 0.034kg Minimum Back Box Depth Suggested Back Box Depth Not Applicable Not Applicable **Fixing Centres** 60.3mm Minimum Access Top 100cm Minimum Access Bottom 100cm **Minimum Access Left** 100cm **Minimum Access Right** 100cm **Minimum Access Front** 100cm **Minimum Access Rear** 100cm

Flush Mounting Metal Box SB655 or CR2201/BG (25mm)

Flush Mounting Dry Lining Box SB619 (35mm) Surface Mounting Box 9047 (29mm)

STANDARDS

British Standard/s BS 5733 Other Markings/Standards CE


PACKAGING

Inner Carton Qty 20 Customer MOQ 20

SUSTAINABILITY

URL to technology list https://www.crabtreecommercial.co.uk/





Electrium Sales Limited
A Siemens Company
Tel: +44 (0) 1543 438310

Fax: +44 (0) 1543 000000 Email: crabtree.technical@electrium.co.uk

www.electrium.co.uk

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this publication, specifications and performance data are constantly changing.

Latest details can be obtained from Crabtree.





86