CR2573/G

3 GANG GRID COVER PLATE IN GREY





CONSTRUCTION

Product CategoryWiring AccessoryProduct GroupPower & ControlProduct TypeGrid SystemShapeRectangular PlateMaterialUrea FormaldehydeFinishMouldedMounting TypeFlush/Surface

POWER

CurrentNot ApplicableCurrent TypeNot ApplicableFrequencyNot ApplicableInput VoltageNot ApplicableSwitched PolesNot ApplicableNumber of Rocker Switches0Number of WaysNot ApplicableFuse RatingNot Applicable

AESTHETICS

Plate Gang / Module Size 3 Gang
Plate Colour Grey
Rocker Colour Not Applicable
Light Reflectance Value (LRV) 8
Printing Text/Type Not Applicable
Status Indicator N
Switched Outlets N
Part M Compliance Y
Anti Microbial Properties Y

Key Features & BenefitsCurved Slimline Plate
Front Fixed & Screw Retained

TERMINAL

L & N Terminal Capacity as per BS Standard
Earth Terminal Capacity as per BS Standard
Number of Earth Terminals
Cable Strip Length
Screwdriver Type Required
Torque requirement as per BS Standard L&N
Torque requirement as per BS Standard Earth
Not Applicable
Not Applicable
Not Applicable

LOCATION

Max Ambient Operating Temp as per BS Req.Not ApplicableMin Ambient Operating Temp as per BS Req.Not ApplicableMax Altitude as per BS Requirement2000mIP RatingIP2X (Full Instinct Grid Assembly)

DIMENSIONAL / FIXING

Height 86mm Width 146mm Depth Overall (Inc Rocker) 9mm Not Applicable **Depth Interior only** Gross Weight 0.062kg Minimum Back Box Depth Suggested Back Box Depth Not Applicable Not Applicable **Fixing Centres** 120.6mm Minimum Access Top 100cm Minimum Access Bottom 100cm **Minimum Access Left** 100cm **Minimum Access Right** 100cm **Minimum Access Front** 100cm **Minimum Access Rear** 100cm Flush Mounting Metal Box SB665 (25mm) Flush Mounting Dry Lining Box SB629 (35mm) **Surface Mounting Box** 9048 (29mm)

STANDARDS


British Standard/s BS 5733 Other Markings/Standards CE


PACKAGING

Inner Carton Qty 10 Customer MOQ 10


SUSTAINABILITY

URL to technology list https://www.crabtreecommercial.co.uk/





146



Electrium Sales Limited
A Siemens Company
Tel: +44 (0) 1543 438310

Fax: +44 (0) 1543 000000 Email: crabtree.technical@electrium.co.uk

www.electrium.co.uk

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this publication, specifications and performance data are constantly changing.

Latest details can be obtained from Crabtree.



