CR2578/BG

8 GANG GRID COVER PLATE METALCLAD





CONSTRUCTION

Product CategoryWiring AccessoryProduct GroupPower & ControlProduct TypeGrid SystemShapeSquare PlateMaterialMild SteelFinishPowder CoatedMounting TypeFlush/Surface

POWER

CurrentNot ApplicableCurrent TypeNot ApplicableFrequencyNot ApplicableInput VoltageNot ApplicableSwitched PolesNot ApplicableNumber of Rocker Switches0Number of WaysNot ApplicableFuse RatingNot Applicable

AESTHETICS

 Plate Gang / Module Size
 8 Gang

 Plate Colour
 Birch Grey

 Rocker Colour
 Not Applicable

 Light Reflectance Value (LRV)
 29

 Printing Text/Type
 Not Applicable

 Status Indicator
 N

 Switched Outlets
 N

Status indicator N
Switched Outlets N
Part M Compliance Y
Anti Microbial Properties N
Key Footures 8 Panelits

Key Features & BenefitsCurved Slimline Plate
Front Fixed & Screw Retained

TERMINAL

L & N Terminal Capacity as per BS Standard
Earth Terminal Capacity as per BS Standard
Number of Earth Terminals
Cable Strip Length
Screwdriver Type Required
Torque requirement as per BS Standard L&N
Torque requirement as per BS Standard Earth
Not Applicable
Not Applicable
Not Applicable

LOCATION

Max Ambient Operating Temp as per BS Req. Not Applicable
Min Ambient Operating Temp as per BS Req. Not Applicable
Max Altitude as per BS Requirement
IP Rating

Not Applicable
Not Applicable
2000m
IP2X (Full Instinct Grid Assembly)

DIMENSIONAL / FIXING

Height 146mm Width 146mm Depth Overall (Inc Rocker) 9mm **Depth Interior only** Not Applicable Gross Weight 0.164kg Minimum Back Box Depth Suggested Back Box Depth Not Applicable Not Applicable **Fixing Centres** 132mm Minimum Access Top 100cm Minimum Access Bottom 100cm **Minimum Access Left** 100cm **Minimum Access Right** 100cm **Minimum Access Front** 100cm **Minimum Access Rear** 100cm

Flush Mounting Metal Box CR2206 (35mm)
Flush Mounting Dry Lining Box Not Applicable

Surface Mounting Box CR2206/BG (40mm with knockouts)

STANDARDS


BS 5733 Other Markings/Standards CE


PACKAGING

Inner Carton Qty 1
Customer MOQ 1

SUSTAINABILITY

URL to technology list https://www.crabtreecommercial.co.uk/





Electrium Sales Limited
A Siemens Company
Tel: +44 (0) 1543 438310
Fax: +44 (0) 1543 000000

Fax: +44 (0) 1543 000000 Email: crabtree.technical@electrium.co.uk

www.electrium.co.uk

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this publication, specifications and performance data are constantly changing.

Latest details can be obtained from Crabtree.



©rabtree