# CR2592/WH

2 GANG ARCHITRAVE COVER PLATE

## CONSTRUCTION

Product Category Product Group Product Type Shape Material Finish Mounting Type

## POWER

Current Current Type Frequency Input Voltage Switched Poles Number of Rocker Switches Number of Ways Fuse Rating

## **AESTHETICS**

Plate Gang / Module Size Plate Colour Rocker Colour Light Reflectance Value (LRV) Printing Text/Type Status Indicator Switched Outlets Part M Compliance Anti Microbial Properties Key Features & Benefits

#### **TERMINAL**

L & N Terminal Capacity as per BS Standard Earth Terminal Capacity as per BS Standard Number of Earth Terminals Cable Strip Length Screwdriver Type Required Torque requirement as per BS Standard L&N Torque requirement as per BS Standard Earth

#### **LOCATION**

Max Ambient Operating Temp as per BS Req. Min Ambient Operating Temp as per BS Req. Max Altitude as per BS Requirement IP Rating

#### **DIMENSIONAL / FIXING**

Height Width Depth Overall (Inc Rocker) Depth Interior only Gross Weight Minimum Back Box Depth Suggested Back Box Depth **Fixing Centres** Minimum Access Top Minimum Access Bottom **Minimum Access Left Minimum Access Right Minimum Access Front Minimum Access Rear** Flush Mounting Metal Box Flush Mounting Dry Lining Box Surface Mounting Box

### **STANDARDS**

British Standard/s Other Markings/Standards

#### PACKAGING

Inner Carton Qty Customer MOQ

#### **SUSTAINABILITY**

URL to technology list

Wiring Accessory Ancillary Item Grid System Rectangular Plate Urea Formaldehyde Moulded Flush/Surface

**Building Information Modelling** 

WIRING

Not Applicable Not Applicable Not Applicable Not Applicable O Not Applicable Not Applicable

2 Gang Architrave White Not Applicable 74 Not Applicable N N Y Y Curved Slimline Plate Front Fixed & Screw Retained

Not Applicable Not Applicable O Not Applicable Slotted Type Not Applicable Not Applicable

Not Applicable Not Applicable 2000m IP2X (Full Instinct Grid Assembly)

146.5mm 32.5mm 9mm Not Applicable 0.032kg Not Applicable Not Applicable 120.6mm 100cm 100cm 100cm 100cm 100cm 100cm 9258 (28mm) Not Applicable 4006 (20mm)

BS 5733 CE

20

20

https://www.crabtreecommercial.co.uk/

Electrium Sales Limited A Siemens Company Tel: +44 (0) 1543 438310 Fax: +44 (0) 1543 000000 Email: crabtree.technical@electrium.co.uk

www.electrium.co.uk

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this publication, specifications and performance data are constantly changing. Latest details can be obtained from Crabtree.

**C**rabtree