



HMF199T



HMF299T



HMF399T



HMF499T

MCBs 80 - 125A

- Suitable for isolation (according to BS EN 60947-2). The isolation of the circuit breakers is indicated by a green indicator on the toggle.

Standards

- 10 kA: BS EN 60898-1, 10 kA BS EN 60947-2
- 15 kA: BS EN 60898-1, 15 kA BS EN 60947-2
- I_n 80 to 125A

Connection Capacity

- 35mm² flexible (50mm² possible with some cable pin lugs).
- 70mm² rigid.

Nominal Voltage

- 230/415 V a.c.
- Calibration setting: 30 °C
- (BS EN 60898-1)
- Insulation voltage: 500 V

Lockable Toggle

- MCB can be locked in "Off" position by the integrated locking facility on the toggle.
- This lock allows the insertion of a 2.5-3.5mm plastic cable tie where you can fit a warning card if necessary, allowing a safer working environment.
- Compatible with RCD Add-On Blocks.

Rating	Width (1 = 17.5mm)	Cat ref. 10kA C Curve	Cat ref. 15kA C Curve	Cat ref. 15kA D Curve
Single Pole MCBs				
80A	1 ½ Mod	HMF180T	HMC180T	HMD180T
100A	1 ½ Mod	HMF190T	HMC190T	HMD190T
125A	1 ½ Mod	HMF199T	HMC199T	HMD199T
Double Pole MCBs				
80A	3 Mod	HMF280T	HMC280T	HMD280T
100A	3 Mod	HMF290T	HMC290T	HMD290T
125A	3 Mod	HMF299T	HMC299T	HMD299T
Triple Pole MCBs				
80A	4 ½ Mod	HMF380T	HMC380T	HMD380T
100A	4 ½ Mod	HMF390T	HMC390T	HMD390T
125A	4 ½ Mod	HMF399T	HMC399T	HMD399T
Four Pole MCBs				
80A	6 Mod	HMF480T	HMC480T	HMD480T
100A	6 Mod	HMF490T	HMC490T	HMD490T
125A	6 Mod	HMF499T	HMC499T	HMD499T



MZN130

Terminal Covers Screw Cap

Description

To cover connection terminals and screws of circuit breaker. The screw covers can be sealed.

Cat ref.

MZN130



MZN131

Phase Barrier

Description

1 Set of 3 Phase Separators

Cat ref.

MZN131