

Accessories for x250 Devices

Indication contacts

- 1 changeover switch (ON/OFF): indicates the position of the MCCB "open" or "close".
- 1 changeover alarm contact: indicates MCCB tripped.

Coil connection

- Connection capacity: 0.75 mm² flexible or rigid cables
- The cable capacity of the terminals is 0.5 to 1.25mm².

Shunt trip

- Remote tripping of MCCBs
- Operating voltage: 0.7 to 1.1 x U_n

Under voltage release

- Enables tripping of MCCBs or moulded case switches when voltage level drop between 35 and 70% of U_n. Pick up voltage 0.85 x U_n
- Padlockable direct rotary handle is equipped with front cover and handle, fixing without additional screws.



HXA021H

HXA024H



HXA014H


Description	Cat ref.
Auxiliary Contacts	
1 Changeover contact (On/Off), 250V a.c. / 3A, 125V d.c. / 0.4A, 1 NO+ 1NC	HXA021H
1 Changeover alarm contact, 250 V a.c. / 3A, 125 V d.c. / 0.4A, NO + 1 NC	HXA024H
Low level contact (On/Off), 125V a.c. , NO + 1 NC	HXA025H
Low Level alarm contact, 125 V a.c. , NO + 1 NC	HXA026H
Shunt Trips	
24V DC	HXA001H
48V DC	HXA002H
100-120V a.c.	HXA003H
200-240V a.c.	HXA004H
380-450V a.c.	HXA005H
Undervoltage Releases	
24V DC	HXA011H
100-120V a.c.	HXA013H
200-240V a.c.	HXA014H
380-450V a.c.	HXA015H
Delayed Undervoltage Releases	
24V DC	HXA051H
100-120V a.c.	HXA053H
200-240V a.c.	HXA054H
380-450V a.c.	HXA055H
Accessories	
Locking Device to Mount on MCCB for Handle Locking for 3 Padlock Max ø 8mm	HXA039H
Set of Four Extended Straight Connections	HXB010H
Set of Four Extended Spreader Connections	HYB011H
Set of Three Interphase Barriers	HYB019H
Pair of Terminal Covers for Extended Straight Connections	HYB021H
Pair of Terminal Covers for Extended Spreader Connections	HYB023H



HXA039H



HYB010H



HYB019H



HYB021H