



IU41

## IU Enclosures

### Characteristics:

- 1 row boxes 1-5 modules.
- Ideally suited for the installation of individual modular devices. (RCCBs, MCBs, RCBOs, switch disconnectors etc).
- Available without door, with plain door or with glazed door.
- Where larger cables need to be accommodated (for switch disconnectors etc.) extra cabling space is provided in the extended height versions (Recommended maximum cable size: extended height = 35mm<sup>2</sup>, all other references = 6mm<sup>2</sup>).
- All boxes from 2-5 modules are fitted with an earth bar as standard and for those with doors the catch can be replaced with the optional key locking facility.
- For dimensions see page 2.38.

Description	Cat ref. Without Door	Cat ref. Plain Door	Cat ref. Glazed Door
2 Modules	<b>IU2</b>	<b>IU2/D</b>	<b>IU2/GD</b>
3 Modules	<b>IU3</b>	<b>IU3/D</b>	-
4 Modules	<b>IU4</b>	<b>IU4/D</b>	-
1 Module Extended Height	<b>IU41</b>	<b>IU41-D</b>	-
2 Modules Extended Height	<b>IU42</b>	<b>IU42/D</b>	-
4 Modules Extended Height	<b>IU44</b>	<b>IU44/D</b>	<b>IU44/GD</b>
5 Modules Extended Height	<b>IU45</b>	-	-

## Accessories for IU Enclosures

Description	Cat ref.
Keylock with 2 Keys Suitable for All <b>IU</b> Enclosures Fitted with Door	<b>IKL1</b>