

### **Orion - Steel Enclosures**

#### Characteristics:

- Steel (1.5mm) IP65 rated enclosure, insulation class: I (RAL 7035).
- Mounting plates and modular chassis' are required for the installation of devices, see page 2.9.
- 2 removable gland plates for cable entry on top and bottom.
- IP65 with door closed, complies with BS EN 60529.
- Earth studs on both body and door.
- Plain, easily removable door equipped with one or two locks with triangular 8mm bit centres.

Options: Key lock, wall fixing brackets, mounting plate, equipment kits for modular devices.

Note: Not suitable for outdoor use.

- For full dimensions see page 2.39.

Description	Dimensions (H x W x D mm)	No. of locks	Cat ref. Plain Door	Cat ref. Glazed Door
IP65 Surface Mount Enclosure	300 x 250 x 160	1	FL102A	-
IP65 Surface Mount Enclosure	350 x 300 x 160	1	FL104A	FL154A
IP65 Surface Mount Enclosure	350 x 300 x 200	1	FL105A	FL155A
IP65 Surface Mount Enclosure	500 x 300 x 200	1	FL110A	FL160A
IP65 Surface Mount Enclosure	500 x 400 x 200	1	FL112A	FL162A
IP65 Surface Mount Enclosure	650 x 400 x 200	2	FL117A	FL167A
IP65 Surface Mount Enclosure	650 x 400 x 250	2	FL118A	FL168A
IP65 Surface Mount Enclosure	650 x 500 x 250	2	FL120A	FL170A
IP65 Surface Mount Enclosure	800 x 600 x 300	2	FL124A	FL174A
IP65 Surface Mount Enclosure	950 x 600 x 300	2	FL126A	FL176A
IP65 Surface Mount Enclosure	950 x 800 x 300	2	FL128A	FL178A



FL110A

## **Orion - GRP Enclosures**

#### Characteristics:

- GRP IP65 rated enclosure, (RAL 7035). Door made of glass reinforced polyester (GRP).
- Mounting plates and modular chassis' are required for the installation of devices, see page 2.9.
- IP65 with door closed, complies with BS EN 60529.
- Earth studs on both body and door.
- Plain, easily removable door equipped with one or two locks with triangular 8mm bit centres.

**Options:** Key lock, wall fixing brackets, mounting plate, equipment kits for modular devices.

- **Note:** Not suitable for outdoor use.
- FL201B made of polycarbonate.For full dimensions see page 2.40.

Description	Dimensions (H x W x D mm)	No. of locks	Cat ref. Plain Door	Cat ref. Glazed Door
IP65 Surface Mount Enclosure	350 x 300 x 160	1	FL204B	FL254B
IP65 Surface Mount Enclosure	500 x 300 x 200	2	FL209B	FL259B
IP65 Surface Mount Enclosure	500 x 400 x 200	2	FL213B	FL263B
IP65 Surface Mount Enclosure	650 x 400 x 200	2	FL216B	FL266B
IP65 Surface Mount Enclosure	650 x 500 x 250	2	FL221B	FL271B
IP65 Surface Mount Enclosure	800 x 600 x 300	2	FL229B	FL279B
IP65 Surface Mount Enclosure	1200 x 850 x 300	1	FL327B	FL527B



FL216B

# **Orion Accessories**

Description	Cat ref.
Key lock to be mounted on the triangular lock, supplied with 2 keys no 427 for h $\leq$ 800	FL96Z
Key lock to be mounted on the triangular lock, supplied with 2 keys no 427 for h $\leq$ 1150	FL98Z
Replacement lock 1 set of 2 locks with male square 8mm with 1 key	FL81Z
Replacement lock 1 set of locks double-bar 3mm with 1 key	FL97Z
Plastic wall fixing brackets delivered with fixing screws M 6x12 on enclosure set of 4 pieces	FL863Z
Depth adjustment slide for enclosures 300mm	FL672E



FL962



FL80Z



FLO