

Brass Terminals ≤ 60A With Support

Characteristics

- Brass terminals with or without support for neutral/earth/phase connections.

Colour Coded Supports

- Neutral = Blue, Earth = Green/Yellow, Phase = Brown.

- Insulated support can be fitted on DIN rail with **KZ060** rail clip or flat bar 12 x 2mm.



KM04L



KM13N

Connections: number + section	Neutral Cat ref.	Earth Cat ref.	Phase Cat ref.
2 x 16 + 2 x 10mm ² 4 Connections Length 30mm	-	-	KM04L
3 x 16 + 4 x 10mm ² 7 Connections Length 49mm	KM07N	KM07E	KM07L
5 x 16 + 5 x 10mm ² 10 Connections Length 67mm	KM10D	KM10F	-
5 x 16 + 6 x 10mm ² 11 Connections Length 73mm	KM11N	KM11E	KM11L
2 x 16 (Double Drive) + 8 x 10mm ² 10 Connections Length 69mm	KM10N	KM10E	-
6 x 16 + 7 x 10mm ² 13 Connections Length 85mm	KM13N	KM13E	-
1 x 25 + 5 x 16 + 5 x 10mm ² 11 Connections Length 85mm	-	KM11B	-
1 x 25 + 8 x 16 + 8 x 10mm ² 17 Connections Length 121mm	KM17N (2 supports)	KM17E	-
1 x 25 + 11 x 16 + 13 x 10mm ² 25 Connections Length 169mm	KM25N	KM25E	-

Brass Terminals ≤ 60A Without Support

Connections: number + section	Cat ref.
2 x 16 + 2 x 10mm ² 4 Connections Length 30mm	K140
3 x 16 + 4 x 10mm ² 7 Connections Length 49mm	K142
5 x 16 + 5 x 10mm ² 10 Connections Length 67mm	K143
5 x 16 + 6 x 10mm ² 11 Connections Length 73mm	K144
2 x 16 (Double Drive) + 8 x 10mm ² 10 Connections Length 69mm	K145
6 x 16 + 7 x 10mm ² 13 Connections Length 85mm	K148
1 x 25 + 5 x 16 + 5 x 10mm ² 11 Connections Length 85mm	K151
1 x 25 + 8 x 16 + 8 x 10mm ² 17 Connections Length 121mm	K156
1 x 25 + 11 x 16 + 13 x 10mm ² 25 Connections Length 169mm	K158
1 x 25 + 8 x 16 + 29 x 10mm ² Long Length Terminals Length 242mm	K159
1 x 25 + 16 x 16 + 61 x 10mm ² Fixing on Flat Bar	K160F
12 x 2 with Supports Length 482mm	



K144

Terminal Supports (For K140 - K160, terminals insulating material M4 x 8 fixing screws)

Description	Cat ref.
Blue Support for Neutral	KZ012
Green / Yellow Support for Earth	KZ013
Beige Support	KZ014



KZ012

Rail Clip (For fixing terminals on DIN Rails, not for: KM04L, KM10D, KM10F, KM10N, KM10E)

Description	Cat ref.
Mounts on DIN Rail Width 50mm	KZ060



KZ060

Neutral Assembly

Description	Cat ref.
DIN Rail Mounted 5 x 16mm ² and 9 x 10mm ²	KM14N