



KLMB4W

Marshalling Boxes - Wire In, Plug Out

Characteristics:

- The KLMB marshalling box allows the connection and control of multiple luminaires. The marshalling box utilises a robust extruded aluminium body.
- 7 Pole.
- 4, 6, 8, 10 & 12 outlets.
- 16A Rated BS 5733:2010 .
- Short circuit tested: 1500A conditional rating.

Description	Cat ref.
Marshalling Box, Single Supply, Wire In, Plug Out	
4 Way	KLMB4W
6 Way	KLMB6W
8 Way	KLMB8W
10 Way	KLMB10W
12 Way	KLMB12W
Marshalling Box, Dual Channel, Wire In, Plug Out	
8 Way, 4/4	KLMB244W
10 Way, 5/5	KLMB255W
12 Way, 6/6	KLMB266W



KLMB5P

Marshalling Boxes - Plug In, Plug Out

Characteristics:

- The KLMB marshalling box allows the connection and control of multiple luminaires. The marshalling box utilises a robust extruded aluminium body.
- 7 Pole.
- 5, 7, 9 & 11 outlets.
- 16A Rated BS 5733:2010 .
- Short circuit tested: 1500A conditional rating.

Description	Cat ref.
Marshalling Box, Single Supply, Plug In, Plug out	
5 Way	KLMB5P
7 Way	KLMB7P
9 Way	KLMB9P
11 Way	KLMB11P



K7B1M075WPCR

Klik 7 Pre-wired Plugs with Sockets

Characteristics:

- Connections to the luminaire are made via a pre-wired plug and lead. All leads are low smoke zero halogen and are factory connected and tested.
- Standard, digital and emergency luminaires.
- Short circuit tested: 1500A conditional rating.
- Cable standard BS 7211.

Description	Cat ref.
Pre-wired Plugs and Sockets for Standard Luminaires	
6A Luminaire Lead 1.5m 0.75mm ² 3 Core Plug to Wire + KLPCR7	K7B1M075WPCR ★
6A Luminaire Lead 3m 0.75mm ² 3 Core Plug to Wire + KLPCR7	K7B3M075WPCR ★
Pre-wired Plugs and Sockets for Standard Luminaires with Emergency	
6A Luminaire Lead 1.5m 0.75mm ² 4 Core Plug to Wire + KLPCR7	K7J1M075WPCR ★
6A Luminaire Lead 3m 0.75mm ² 4 Core Plug to Wire + KLPCR7	K7J3M075WPCR ★
Pre-wired Plugs and Sockets for Dimmable Luminaires	
6A Luminaire Lead 1.5m 0.75mm ² 5 Core Plug to Wire + KLPCR7	K7P1M075WPCR ★
6A Luminaire Lead 3m 0.75mm ² 5 Core Plug to Wire + KLPCR7	K7P3M075WPCR ★
Pre-wired Plugs and Sockets for Dimmable Luminaires with Emergency	
6A Luminaire Lead 1.5m 0.75mm ² 6 Core Plug to Wire + KLPCR7	K7T1M075WPCR ★
6A Luminaire Lead 3m 0.75mm ² 6 Core Plug to Wire + KLPCR7	K7T3M075WPCR ★