

3 Pin Pre-wired 6A Plugs

Characteristics:

- 6A pre-wired plugs are used to connect luminaires to a Klik ceiling rose or marshalling box. All leads have prepared ends.
- Complies with BS 6972 and BS 5733:2010.
- PVC flexible cord complies with BS EN 50525-2-11.
- Low smoke zero halogen flexible cord, complies with BS EN 50525-3-11.

Description	Quantity	PVC Cat ref.	LSZH Cat ref.
6A Pre-wired Plugs with 0.75mm ² Flexible Cord			
1 Metre	10	P22/1.0	P22/LSF/1.0
2 Metre	10	P22/2.0	P22/LSF/2.0
3 Metre	5	P22/3.0	P22/LSF/3.0
4 Metre	5	P22/4.0	P22/LSF/4.0
6A Pre-wired Plugs with 1mm ² Flexible Cord			
2 Metre	10	P22/1.0PVC/2	P22/1.0LSF/2
3 Metre	5	P22/1.0PVC/3	P22/1.0LSF/3
4 Metre	5	P22/1.0PVC/4	P22/1.0LSF/4
5 Metre	5	P22/1.0PVC/5	P22/1.0LSF/5



P22/1.0

4 Pin (Including Auxiliary) Pre-wired 6A Plugs - White

Characteristics:

- Klik auxiliary 6A pre-wired plugs are used to connect luminaires to a Klik ceiling rose or marshalling box.
- Complies with BS 6972 and BS 5733:2010.
- PVC flexible cord complies with BS EN 50525-2-11.
- Low smoke zero halogen flexible cord, complies with BS EN 50525-3-11.
- All leads have prepared ends.

Description	Quantity	PVC Cat ref.	LSZH Cat ref.
6A Pre-wired Plugs with 0.75mm ² Flexible Cord			
1 Metre	10	P64AX/1.0	P64AX/LSF/1.0
2 Metre	10	P64AX/2.0	P64AX/LSF/2.0
3 Metre	5	P64AX/3.0	P64AX/LSF/3.0
4 Metre	5	P64AX/4.0	P64AX/LSF/4.0
6A Pre-wired Plugs with 1mm² Flexible Cord			
2 Metre	10	P64AX/1.0PVC/2	P64AX/1.0LSF/2
3 Metre	5	P64AX/1.0PVC/3	P64AX/1.0LSF/3
4 Metre	5	P64AX/1.0PVC/4	P64AX/1.0LSF/4
5 Metre	5	P64AX/1.0PVC/5	P64AX/1.0LSF/5



P64AX/1.0

4 Pin (Including Auxiliary) Pre-wired 6A Plugs - Red

Characteristics:

- Klik auxiliary 6A pre-wired plugs are used to connect luminaires to a Klik ceiling rose or marshalling box.
- Complies with BS 6972 and BS 5733:2010.
- PVC flexible cord complies with BS EN 50525-2-11.
- Low smoke zero halogen flexible cord, complies with BS EN 50525-3-11.
- All leads have prepared ends.

Description	Quantity	PVC Cat ref.	LSZH Cat ref.
6A Pre-wired Plugs with 0.75mm ² Flexible Cord			
1 Metre	10	P64AXR/1.0	P64AXR/LSF/1.0
2 Metre	10	P64AXR/2.0	P64AXR/LSF/2.0
3 Metre	5	P64AXR/3.0	P64AXR/LSF/3.0
4 Metre	5	P64AXR/4.0	P64AXR/LSF/4.0
6A Pre-wired Plugs with 1mm ² Flexible Cord			
2 Metre 1.00mm² Flexible Cord	10	P64AXR/1.0PVC/2	P64AXR/1.0LSF/2
3 Metre 1.00mm² Flexible Cord	5	P64AXR/1.0PVC/3	P64AXR/1.0LSF/3
4 Metre 1.00mm² Flexible Cord	5	P64AXR/1.0PVC/4	P64AXR/1.0LSF/4
5 Metre 1.00mm² Flexible Cord	5	P64AXR/1.0PVC/5	P64AXR/1.0LSF/5



P64AXR/1.0