



PCR2000

### 3 Pin Plug-in Ceiling Rose & Cover

**Characteristics:**

- The 6A plug-in ceiling rose is used to offer a pluggable connection for luminaires. The luminaire can be connected and disconnected under load.
- Complies with BS 5733:2010.
- Sockets have 4 terminations: line, neutral, CPC and loop-in.
- Plugs have 3 terminations: line, neutral and CPC.
- Fixing: 50.8mm Standard Diagonal (BESA).

Description	Quantity	Cat ref.
3 Pin Plug-in Ceiling Rose White	10	<b>PCR2000</b>



CR64AX/R

### 4 Pin (including Auxiliary) Plug-in Ceiling Rose & Cover

**Characteristics:**

- Klik 6A pre-wired plug-in ceiling roses are used to connect luminaires to a fixed wiring installation. Auxiliary contact available, a typical use is for emergency lighting.
- Complies with BS 6972 and BS 5733:2010.
- Sockets have 5 terminations: line, neutral, CPC, auxiliary and loop-in.
- Plugs have 4 terminations: line, neutral, CPC and auxiliary.

Description	Quantity	Cat ref.
4 Pin Plug-in Ceiling Rose White	10	<b>CR64AX</b>
4 Pin Plug-in Ceiling Rose Red	10	<b>CR64AX/R</b>



A1/R

### Spare Ceiling Rose Cover

Description	Quantity	Cat ref.
Ceiling Rose Cover White	10	<b>A1</b>
Ceiling Rose Cover Red	10	<b>A1/R</b>



P22

### 3 Pin Plug

**Characteristics:**

- Klik 3 pin plugs are used to connect into a Klik socket giving a pluggable connection to luminaires.
- Complies with BS 6972 and BS 5733:2010.
- Suitable for use with any Klik 3 or 4 pin socket.
- **P22** plug is supplied in a plug-in ceiling rose, cat ref. **PCR2000**.
- Plugs have 3 terminations: line, neutral and CPC.

**Warning:** Plugs must not be fitted on the supply side of any installation - they must be connected to the load / fitting / appliance side of the installation.

Description	Quantity	Cat ref.
3 Pin Plug White	10	<b>P22</b>



P64AX

### 4 Pin (Including Auxiliary) Plug

**Characteristics:**

- Klik plugs with auxiliary pin are used to connect into the Klik sockets giving a pluggable connection to luminaires.
- Complies with BS 6972 and BS 5733:2010.
- Suitable for use with any Klik 4 pin sockets.
- **P64AX** plug is supplied in a plug-in ceiling rose, Cat. ref. **CR64AX**.
- Plugs have 4 terminations: line, neutral, CPC and auxiliary.

**Warning:** Plugs must not be fitted on the supply side of any installation - they must be connected to the load / fitting / appliance side of the installation.

Description	Quantity	Cat ref.
4 Pin Plug White	10	<b>P64AX</b>
4 Pin Plug Red	10	<b>P64AX/R</b>