



WMSS82



WMS51



WMSS82USB

### Switched & Unswitched Socket Outlets

#### Characteristics:

- Unique patented three part safety shutter.
- Complies with BS 1363-2, a.c only.
- Double pole switching mechanism on switched sockets.
- Twin socket comes with twin earth as standard.
- All terminal screws grouped in-line and upward facing for ease of installation.
- Clear printed and engraved terminal markings.
- Capacity of each terminal: 3 x 4mm<sup>2</sup> conductors switched & unswitched (for other sized conductors see terminal capacities on page 5.48).
- **WMSS82USB(S) - Warning:** To avoid possible damage to the product or spurious insulation readings, please disconnect the product before carrying out insulation resistance testing.
- **WMSS82USB(S)** USB output: 5V d.c. 2.4A total max.
- For mounting boxes see selection chart on page 5.47.
- Supplied with M3.5 x 30mm long fixing screws.

Description	Cat ref.
<b>Switched Socket Outlets</b>	
13A 1 Gang Double Pole	<b>WMSS81</b>
13A 2 Gang Double Pole Dual Earth	<b>WMSS82</b>
13A 2 Gang Double Pole Dual Earth & Two USB Ports	<b>WMSS82USB</b>
13A 2 Gang Double Pole Dual Earth & Two USB Ports & 10mm Spacer	<b>WMSS82USBS</b>
10mm Spacer for 2 Gang Sockets	<b>WMUSBS</b>
13A 2 Gang Double Pole Dual Earth Outboard Rockers	<b>WMSS82O</b>
13A 1 Gang Double Pole with LED Indicator	<b>WMSS81N</b>
13A 2 Gang Double Pole Dual Earth with LED Indicator	<b>WMSS82N</b>
13A 2 Gang Double Pole Dual Earth Outboard Rockers & LED Indicator	<b>WMSS82ON</b>
15A 1 Gang	<b>WMSS115</b>
<b>Unswitched Socket Outlets</b>	
13A 1 Gang	<b>WMS81</b>
13A 2 Gang Dual Earth	<b>WMS82</b>
5A 1 Gang	<b>WMS51</b>



WMCC50



WMCC50N

### Cooker Control Unit

#### Characteristics:

- Complies with BS 4177.
- Switch and socket are double pole.
- Twin earth as standard.
- Main switch is suitable for isolation.
- All terminals are upward facing for ease of installation.
- Clearly printed terminal marking.
- Capacity of terminals: 2 x 6.0mm<sup>2</sup>, 1 x 16.0mm<sup>2</sup>.
- For mounting boxes see selection chart on page 5.47.
- Supplied with M3.5 x 30mm long fixing screws.

Description	Cat ref.
45A Cooker Control Unit	<b>WMCC50</b>
45A Cooker Control Unit with LED Indicator	<b>WMCC50N</b>

### Outlet Plates

#### Characteristics:

- Complies with BS 5733
- Terminal capacity: 20A 2 x 6.0mm<sup>2</sup>, 45A 2 x 10.0mm<sup>2</sup> conductors
- 20A plate features 2 separate terminals for each of Line, Neutral and Earth so flexible and fixed wiring do not occupy the same terminal.
- Single screw fast fix cable clamp.
- Supplied with M3.5 x 30mm long fixing screws.
- 45A features large open brass terminals for ease of installation.
- Protective red washer must be used under cable clamp to prevent damage to cable.



WMP2FO

Description	Cat ref.
<b>Outlet Plates</b>	
20A Flex Outlet Plate	<b>WMP2FO</b>
45A Cooker Cable Outlet with Terminals	<b>WMP50FO</b>