

Isolator Switches Raised Plate

Characteristics:

- Complies with BS EN 60669-2-4.
- Capacity of each terminal 2 x 4.0mm² conductors.
- For mounting boxes see selection chart on page 5.47.
- WR references supplied with M3.5 x 30mm long fixing screws.
- WF references supplied with M3.5 x 20mm long fixing screws.

| Description | Cat ref. White Insert | Cat ref. Black Insert |
|---|-----------------------|-----------------------|
| Raised Plate 3 Pole Fan Isolator Switch | | |
| Polished Steel | WRPS3PIPSW | WRPS3PIPSB |
| Brushed Steel | WRPS3PIBSW | WRPS3PIBSB |
| Polished Brass | WRPS3PIPBW | WRPS3PIPBB |
| Black Nickel | - | WRPS3PIBNB |

OFF ON - ISOLATOR

WFPS3PIBNB

WRPS3PIPSW

Isolator Switches Flat Plate

| Description | Cat ref. White Insert | Cat ref. Black Insert |
|---------------------------------------|-----------------------|-----------------------|
| Flat Plate 3 Pole Fan Isolator Switch | | |
| Polished Steel | WFPS3PIPSW | WFPS3PIPSB |
| Brushed Steel | WFPS3PIBSW | WFPS3PIBSB |
| Polished Brass | WFPS3PIPBW | WFPS3PIPBB |
| Black Nickel | - | WFPS3PIBNB |

Socket Outlets Raised Plates


Characteristics:

- Unique patented three part safety shutter.
- Complies with BS 1363 Part 2, a.c only.
- Double pole switching mechanism on switched sockets.
- Twin socket comes with twin earth as standard.
- All terminals are upward facing with clearly printed terminal markings for ease of installation.
- Capacity of each terminal: 3 x 4mm² conductors, switched & unswitched (for other sized conductors see terminal capacities on page 5.48).
- For mounting boxes see selection chart on page 5.47.
- WR references supplied with M3.5 x 30mm long fixing screws.
- WF references supplied with M3.5 x 20mm long fixing screws.
- Sockets with USB connections Warning: To avoid possible damage to the product or spurious insulation readings, please disconnect the product before carrying out insulation resistance testing.
- Sockets with USB connections: USB output: 5V d.c. 2.4A total max.
- All decorative USB sockets come with spacer colour matched to insert and 30mm & 20mm screws.

| Description | Cat ref. White Insert | Cat ref. Black Insert |
|---|-----------------------|-----------------------|
| Raised Plate 1 Gang Double Pole Switched Socket | | |
| Polished Steel | WRSS81PSW | WRSS81PSB |
| Brushed Steel | WRSS81BSW | WRSS81BSB |
| Polished Brass | WRSS81PBW | WRSS81PBB |
| Black Nickel | _ | WRSS81BNB |

Raised Plate 2 Gang Double Pole Switched Socket Dual Earth

| Polished Steel | WRSS82PSW | WRSS82PSB |
|----------------|-----------|-----------|
| Brushed Steel | WRSS82BSW | WRSS82BSB |
| Polished Brass | WRSS82PBW | WRSS82PBB |
| Black Nickel | - | WRSS82BNB |



| Polished Steel | WRS51PSW | WRS51PSB |
|----------------|----------|----------|
| Brushed Steel | WRS51BSW | WRS51BSB |
| Polished Brass | WRS51PBW | WRS51PBB |
| Black Nickel | - | WRS51BNB |

Raised Plate 2 Gang Double Pole Dual Earth Switched Socket & Two USB Ports

| Polished Steel | WRSS82PSW-USB WRSS82PSB-USB |
|----------------|-----------------------------|
| Brushed Steel | WRSS82BSW-USB WRSS82BSB-USB |
| Polished Brass | WRSS82PBW-USB WRSS82PBB-USB |
| Black Nickel | WRSS82BNB-USB |



WRSS81PBW



WRSS81BNB



WRSS82PBB



WRSS82PSW-USB