



WFSS81BSW



WFSS82PBW



WFSS82BNB-USB



WFSS82BSW-USB

Socket Outlets Flat Plates

Description	Cat ref. White Insert	Cat ref. Black Insert
Flat Plate 1 Gang Double Pole Switched Socket		
Polished Steel	WFSS81PSW	WFSS81PSB
Brushed Steel	WFSS81BSW	WFSS81BSB
Polished Brass	WFSS81PBW	WFSS81PBB
Black Nickel	-	WFSS81BNB

Flat Plate 2 Gang Double Pole Switched Socket Dual Earth

Polished Steel	WFSS82PSW	WFSS82PSB
Brushed Steel	WFSS82BSW	WFSS82BSB
Polished Brass	WFSS82PBW	WFSS82PBB
Black Nickel	-	WFSS82BNB

Flat Plate 5A 1 Gang Unswitched Socket

Polished Steel	WFS51PSW	WFS51PSB
Brushed Steel	WFS51BSW	WFS51BSB
Polished Brass	WFS51PBW	WFS51PBB
Black Nickel	-	WFS51BNB

Raised Plate 2 Gang Double Pole Dual Earth Switched Socket & Two USB Ports

Polished Steel	WFSS82PSW-USB	WFSS82PSB-USB
Brushed Steel	WFSS82BSW-USB	WFSS82BSB-USB
Polished Brass	WFSS82PBW-USB	WFSS82PBB-USB
Black Nickel		WFSS82BNB-USB



WRCC50NPSB



WRCC50NBNB

Cooker Control Unit Raised Plate

Characteristics:

- Complies with BS 4177.
- Switch and socket are double pole with twin earth as standard.
- Main switch is suitable for isolation.
- All terminals are upward facing with clearly printed terminal markings for ease of installation.
- Capacity of terminals 2 x 6.0mm², 1 x 16.0mm².
 For mounting boxes see selection chart on page 5.47.
- WR references supplied with M3.5 x 30mm long fixing screws. WF references supplied with M3.5 x 20mm long fixing screws.

Description	Cat ref. White Insert	Cat ref. Black Insert
Raised Plate 45A Cooker Control Unit		
Polished Steel	WRCC50NPSW	WRCC50NPSB
Brushed Steel	WRCC50NBSW	WRCC50NBSB
Polished Brass	WRCC50NPBW	WRCC50NPBB
Black Nickel	-	WRCC50NBNB



WFCC50NPSW

Cooker Control Unit Flat Plate

Description	Cat ref. White Insert Cat ref. Black Insert
Flat Plate 45A Cooker Control Unit	
Polished Steel	WFCC50NPSW WFCC50NPSB
Brushed Steel	WFCC50NBSW WFCC50NBSB
Polished Brass	WFCC50NPBW WFCC50NPBB
Black Nickel	- WFCC50NBNB