

Fused Connection Units Raised Plate

Characteristics:

- Complies with BS 1363-4.
- Single screw fast fix cable clamp accommodates up to 1.5mm² flexible cord.
- All terminals are upward facing with clearly printed terminal markings for ease of installation.
- Capacity of each terminal 2 x 6.0 mm² conductors.
- For mounting boxes see selection chart on page 5.47.
- WR references supplied with M3.5 x 30mm long fixing screws.
- WF references supplied with M3.5 x 20mm long fixing screws.

Description	Cat ref. White Insert	Cat ref. Black Insert
-------------	-----------------------	-----------------------

Raised Plate 13A FCU Switched

Polished Steel	WRSSU83PSW	WRSSU83PSB
Brushed Steel	WRSSU83BSW	WRSSU83BSB
Polished Brass	WRSSU83PBW	WRSSU83PBB
Black Nickel	-	WRSSU83BNB



WRSSU83FOBSW

Raised Plate 13A FCU Switched with Flex Outlet

Polished Steel	WRSSU83FOPSW	WRSSU83FOPSB
Brushed Steel	WRSSU83FOBSW	WRSSU83FOBSB
Polished Brass	WRSSU83FOPBW	WRSSU83FOPBB
Black Nickel	-	WRSSU83FOBNB



WRSSU83PBB

Raised Plate 13A FCU Unswitched

Polished Steel	WRSU83PSW	WRSU83PSB
Brushed Steel	WRSU83BSW	WRSU83BSB
Polished Brass	WRSU83PBW	WRSU83PBB
Black Nickel	-	WRSU83BNB

Fused Connection Units Flat Plate

Description	Cat ref. White Insert	Cat ref. Black Insert
-------------	-----------------------	-----------------------

Flat Plate 13A FCU Switched

Polished Steel	WFSSU83PSW	WFSSU83PSB
Brushed Steel	WFSSU83BSW	WFSSU83BSB
Polished Brass	WFSSU83PBW	WFSSU83PBB
Black Nickel	-	WFSSU83BNB



WFSU83BSW

Flat Plate 13A FCU Switched with Flex Outlet

Polished Steel	WFSSU83FOPSW	WFSSU83FOPSB
Brushed Steel	WFSSU83FOBSW	WFSSU83FOBSB
Polished Brass	WFSSU83FOPBW	WFSSU83FOPBB
Black Nickel	-	WFSSU83FOBNB



WFSSU83FOBNB

Flat Plate 13A FCU Unswitched

Polished Steel	WFSU83PSW	WFSU83PSB
Brushed Steel	WFSU83BSW	WFSU83BSB
Polished Brass	WFSU83PBW	WFSU83PBB
Black Nickel	-	WFSU83BNB