

Metalclad Socket Outlets

Characteristics:

- Unique patented three part safety shutter.
- Complies with BS 1363-2, a.c. only.
- Double pole switching mechanism on switched sockets.
- Twin socket comes with twin earth as standard.
- Terminal screws grouped in-line and upward facing for ease of installation with clear printed and engraved terminal markings.
- Capacity of each terminal: 5 x 2.5mm² conductors switched; 4 x 2.5mm² unswitched (for other sized conductors see terminal capacities on page 5.48).
- **Sockets with USB - Warning:** To avoid possible damage to the product or spurious insulation readings, please disconnect the product before carrying out insulation resistance testing.
- **Sockets with USB** - USB output: 5V d.c. 2.4A total max.



WPSS81W

Description	Cat ref. Plate Only	Cat ref. With Backbox Without Knockouts	Cat ref. With Backbox With Knockouts
Switched Socket Outlets White			
1 Gang Double Pole Switched Socket	WPSS81W	WPSS81BW	WPSS81BKOW
1 Gang Double Pole Switched Socket with LED Indicator	WPSS81NW	WPSS81NBW	WPSS81NBKOW
2 Gang Double Pole Switched Socket	WPSS82W	WPSS82BW	WPSS82BKOW
2 Gang Double Pole Switched Socket with LED Indicator	WPSS82NW	WPSS82NBW	WPSS82NBKOW
2 Gang Double Pole Switched Socket Outboard Rockers	WPSS82OW	WPSS82OBW	WPSS82OBKOW
2 Gang Double Pole Switched Socket with Two USB Ports	WPSS82W-USB	WPSS82BW-USB	WPSS82BKOW-USB



WPSS81

Switched Socket Outlets Grey

Description	Cat ref. Plate Only	Cat ref. With Backbox Without Knockouts	Cat ref. With Backbox With Knockouts
1 Gang Double Pole Switched Socket	WPSS81	WPSS81B	WPSS81BKO
1 Gang Double Pole Switched Socket with LED Indicator	WPSS81N	WPSS81NB	WPSS81NBKO
2 Gang Double Pole Switched Socket	WPSS82	WPSS82B	WPSS82BKO
2 Gang Double Pole Switched Socket with LED Indicator	WPSS82N	WPSS82NB	WPSS82NBKO
2 Gang Double Pole Switched Socket Outboard Rockers	WPSS82O	WPSS82OB	WPSS82OBKO
2 Gang Double Pole Switched Socket with Two USB Ports	WPSS82-USB	WPSS82B-USB	WPSS82BKO-USB



WPSS82W-USB

Metalclad Fuse Connection Units

Characteristics:

- Complies with BS 1363-4.
- Single screw fast fix cable clamp accommodates up to 1.5mm² flexible cord.
- All terminals are upward facing with clearly printed terminal markings for ease of installation.
- Capacity of each terminal 2 x 6.0 mm² conductors.

Description	Cat ref. Plate Only	Cat ref. With Backbox Without Knockouts	Cat ref. With Backbox With Knockouts
Fuse Connection Units White			
13A FCU Unswitched with Flex Outlet	WPSU83FOW	WPSU83FOBW	WPSU83FOBKOW
13A FCU Switched with Flex Outlet	WPSSU83FOW	WPSSU83FOBW	WPSSU83FOBKOW
13A FCU Switched with LED Indicator & Flex Outlet	WPSSU83FONW	WPSSU83FONBW	WPSSU83FONBOW



WPSU83FOW

Fuse Connection Units Grey

13A FCU Unswitched with Flex Outlet	WPSU83FO	WPSU83FOB	WPSU83FOBKO
13A FCU Switched with Flex Outlet	WPSSU83FO	WPSSU83FOB	WPSSU83FOBKO
13A FCU Switched with LED Indicator & Flex Outlet	WPSSU83FON	WPSSU83FONB	WPSSU83FONBKO



WPSU83FON