

Super Access Terminal Bank Type Ceiling Rose

Characteristics:

- Capacity of each terminal: 3 x 1.00mm² conductor
- Common base with 'access' batten lampholders.
- Barriers between terminals.
- Flexible pendant cord restraining hooks.
- Fixing centres 50.8mm.
- Feet on base to aid mounting on uneven surfaces.
- Three separate knockouts accept 1, 2 or 3 x 1.5mm² conductors.
- Optional halo RL602 (see below)

Description	Dimensions	Pack qty.	Cat ref.
Three Terminals	81 Diameter x 26 (halo = 108mm diameter)	10	RL624

Low Energy Pendant

Description	Pack qty.	Cat ref.
Low Energy Pendant to accommodate GU10-L1 lamp	1	LEL212/6

Pack qty.

20

10

Cat ref.

MB2

MB326E/MT

Mounting Blocks

Characteristics:

Description

- Capacity of earth terminal for mounting blocks: 3 x 1.5mm².
- Cable knockout entries: MB326E/MT centrally in base. Four on periphery will accept 16mm x 16mm or 16mm x 25mm mini trunking.

Dimensions

81 x 19

84 x 30

r 4	-	
	MB3	26E/MT

LEL212/6

Round Mounting Box with Earth Terminal

Round Surface Box 30mm Deep

Lampholder Skirts

Characteristics:

- Suitable for use with any lampholder or batten lampholder.

Description	Pack qty.	Cat ref.
Short Skirt	50	HAL70
Home Office Shield	50	HAL72

Halo

Description	Pack qty.	Cat ref.
Halo (108mm Diameter)	20	RL602

