


100 A  $I_{nA}$  Consumer unit enabling conformity with 18<sup>th</sup> Edition wiring regulations for overload protection of RCCBs and switches, in any single phase residential application regardless of the current rating of the supply authority fuse. Type A RCCDs are provided, these devices can detect AC sinusoidal waveforms and pulsating DC components.



VSR114



### Switch Disconnecter Incomer



#### Characteristics:

- Metal switch disconnecter incomer consumer units, single row from 10 to 20 outgoing ways.
- All consumer units contain rear cable entry, along with top & bottom knockouts.
- Supplied with a full metal DIN rail, 100A switch disconnecter incomer and a full complement of earth and neutral terminals along with marking labels, busbar, instructions, rear cable protector plate and meter tail clamp.
- Recommended for use with TT systems when utilising RCBO on outgoing circuits.
- References ending in **SPD** come with a Type 2 SPD fitted.
- Conforms to BS EN 61439-3 including Annex ZB (16kA rating).
- Adjustable depth in wall 72mm-92mm.
- For dimensions see page 40.

Description	Size	Cat ref.
10 Way 100A Switch Disconnecter Incomer	4	<b>VSR110</b>
14 Way 100A Switch Disconnecter Incomer	5	<b>VSR114</b>
20 Way 100A Switch Disconnecter Incomer	7	<b>VSR120</b>
12 Way 100A Switch Disconnecter Incomer with Factory Fitted <b>Surge Protection</b>	5	<b>VSR112SPD ★</b>
18 way 100A Switch Disconnecter Incomer with Factory Fitted <b>Surge Protection</b>	7	<b>VSR118SPD ★</b>



VSR910C



with Surge

### Configurable

#### Characteristics:

- Metal split load and configurable consumer units with the ability to protect selected circuits with RCBOs and the remainder of circuits split across two RCCBs. Single row from 10 to 16 outgoing ways.
- All consumer units contain rear cable entry, along with top & bottom knockouts.
- Supplied with a full metal DIN rail, 100A switch disconnecter incomer and 2 Type A RCCBs and a full complement of earth and neutral terminals along with marking labels, busbar, instructions, rear cable protector plate and meter tail clamp.
- References ending in **SPD** come with a Type 2 SPD fitted.
- Conforms to BS EN 61439-3 Including Annex ZB (16kA rating).
- Adjustable depth in wall 72mm-92mm.
- For dimensions see page 40.

Description	Max Unprotected Ways	Size	Cat ref.
10 Way High Integrity Split Load 100A Switch 2x 100A 30mA RCCB	3	5	<b>VSR910CU ★</b>
12 Way High Integrity Split Load 100A Switch 2x 100A 30mA RCCB	3	6	<b>VSR912CU ★</b>
16 Way High Integrity Split Load 100A Switch 2x 100A 30mA RCCB	6	7	<b>VSR916CU ★</b>
8 Way High Integrity 100A Switch 2x 100A 30mA RCCB with Factory Fitted <b>Surge Protection</b>	3	5	<b>VSR908CUSPD ★</b>
10 Way High Integrity 100A Switch 2x 100A 30mA RCCB with Factory Fitted <b>Surge Protection</b>	3	6	<b>VSR910CUSPD ★</b>
14 Way High Integrity 100A Switch 2x 100A 30mA RCCB with Factory Fitted <b>Surge Protection</b>	6	7	<b>VSR914CUSPD ★</b>