

Switch Disconnecter Incomer

Characteristics:

- Metal switch disconnecter incomer consumer units, single row from 10 to 20 outgoing ways.
- All consumer units contain rear cable entry, along with top & bottom knockouts.
- Supplied with a full metal DIN rail, 100A switch disconnecter incomer and a full complement of earth and neutral terminals along with marking labels, busbar, instructions, rear cable protector plate and meter tail clamp.
- Recommended for use with TT systems when utilising RCBO on outgoing circuits.
- Conforms to BS EN 61439-3 including Annex ZB (16kA rating).
- Adjustable depth in wall 72mm-92mm.
- For dimensions see page 41.



VMLF110

Description	Size	Cat ref.
10 Way Flush 100A Switch Disconnecter Incomer	4	VMLF110
14 Way Flush 100A Switch Disconnecter Incomer	5	VMLF114
20 Way Flush 100A Switch Disconnecter Incomer	7	VMLF120



Split Load


Characteristics:

- Metal split load and configurable consumer units, single row from 10 to 16 outgoing ways.
- All consumer units contain rear cable entry, along with top & bottom knockouts.
- Supplied with a full metal DIN rail, 100A switch disconnecter incomer and 2 Type A RCCBs and a full complement of earth and neutral terminals along with marking labels, busbar, instructions, rear cable protector plate and meter tail clamp.
- Conforms to BS EN 61439-3 including Annex ZB (16kA rating).
- Adjustable depth in wall 72mm-92mm.
- For dimensions see page 41.



VMLF910C

Description	Size	Cat ref.
10 Way Flush 100A Switch 2x 100A 30mA Type A RCCB	5	VMLF910C ★
12 Way Flush 100A Switch 2x 100A 30mA Type A RCCB	6	VMLF912C ★
16 Way Flush 100A Switch 2x 100A 30mA Type A RCCB	7	VMLF916C ★



Configurable



Characteristics:

- Metal split load and configurable consumer units with ability to protect selected circuits with RCBOs and the remainder of circuits split across two RCCBs. Single row from 10 to 16 outgoing ways.
- All consumer units contain rear cable entry, along with top & bottom knockouts.
- Supplied with a full metal DIN rail, 100A switch disconnecter incomer and 2 Type A RCCBs and a full complement of earth and neutral terminals along with marking labels, busbar, instructions, rear cable protector plate and meter tail clamp.
- References ending in **SPD** come with a Type 2 SPD fitted.
- Conforms to BS EN 61439-3 Including Annex ZB (16kA rating).
- Adjustable depth in wall 72mm-92mm.
- For dimensions see page 41.



VMLF910CU

Description	Max Unprotected Ways	Size	Cat ref.
10 Way Flush High Integrity 100A Switch 2x 100A 30mA Type A RCCB	3	5	VMLF910CU ★
12 Way Flush High Integrity 100A Switch 2x 100A 30mA Type A RCCB	3	6	VMLF912CU ★
16 Way Flush High Integrity 100A Switch 2x 100A 30mA Type A RCCB	6	7	VMLF916CU ★
8 Way High Integrity 100A Switch 2x 100A 30mA RCCB Type A with Factory Fitted Surge Protection		5	VMLF908CUSPD ★
10 Way High Integrity 100A Switch 2x 100A 30mA RCCB Type A with Factory Fitted Surge Protection		6	VMLF910CUSPD ★
14 Way High Integrity 100A Switch 2x 100A 30mA RCCB Type A with Factory Fitted Surge Protection		7	VMLF914CUSPD ★



with Surge