

Characteristics	250A	400A	630 / 800A	800A
Series	JN2**	JF4**	JF6**/JF8**	JHF8**
Busbar current rating	250A	400A	800A	800A (for 800A MCCB only)
Busbar type	Type B Fully Shrouded Copper			
Busbar rated short-time withstand current	25kA for 1 sec	35kA for 1 sec	35kA for 1 sec	35kA for 1 sec
Internal separation	Form 3A			
Incoming	Up to 250A MCCB, MCS	Up to 400A MCCB, MCS	Up to 630A MCCB, 800A LBS	800A MCCB
Outgoing	16 - 125A max.	16 - 125A max.	16 - 125A 100A - 250A	16 - 125A 100A - 250A
Voltage rating in a.c.	415V	415V	415V	415V
IP Protection	IP30			
Enclosure body type	Steel			
Enclosure paint type	Powder coat Grey White BS 4800 00A01			
Cable entry	Via Gland Plates			
<b>Terminal Connection capacity</b>				
Incoming earth terminal	M8	M10	M10	M10
Incoming neutral terminal	M8	M12	M12	M12
Outgoing earth terminals	Up to 50mm <sup>2</sup>	Up to 50mm <sup>2</sup>	Up to 50mm <sup>2</sup>	Up to 50mm <sup>2</sup>
Outgoing neutral terminals	Up to 50mm <sup>2</sup>	Up to 50mm <sup>2</sup>	16A - 125A: Up to 50mm <sup>2</sup> 100A - 250A: M8 Stud	16A - 125A: Up to 50mm <sup>2</sup> 100A - 250A: M8 Stud
Enclosure earth stud	M8	M10	M10	M10
<b>Installation</b>				
Mounting	Surface (Wall)			