



Switch Fuses

	Dimensions (mm)				
	Width	Height	Depth	Depth with Door	Knockouts
IU44-16	115	187	61.5	-	2 x 25mm
IU44-18	125	312	73.5	-	None
IU44-11	125	312	73.5	-	None
IU44-16-D	125	312	74	96	None
IU44-18-D	125	312	74	96	None
IU44-11-D	125	312	74	96	None

IP65 Enclosed Isolating Switch

All dimensions are in mm and exclude the handle.
Add 27mm to the depth to allow for the handle on 10-25A products.
Add 32mm to the depth to allow for the handle on 40-80A products.

Description	Dimensions (mm)		
	Width	Height	Depth
JG00S 10A TPN	100	136	74
JG01S 16A TPN	100	136	105
JG02S 25A TPN	100	136	105
JG03S 40A TPN	136	201	105
JG04S 63A TPN	136	201	118
JG05S 80A TPN	136	201	118

Enclosed thermal current I_{the}	16	25	40	63	80
Rated insulation voltage U_i (V)	690	690	690	690	690
Rated thermal current I_{the} (A)	25	40	63	80	100
Rated operational current					
AC21 400V I_e (A)	25	40	63	80	100
AC22 400V	16	25	40	63	100
AC22 400V $\cos \phi$ 0.65	16	20	32	63	100
AC23 400V	16	20	32	63	100
AC23 400V $\cos \phi$ 0.35	16	15	25	40	63
Rated operational power					
AC23 230V (kW)	4	5.5	7.5	11	15
AC23 400V	7.5	11	15	22	30
Rated fused short circuit current					
Back-up fuse (A)	63	63	63	80	100
R.M.S value I_k (kA)	50	50	50	50	50
Peak value (kA)	5.4	6.6	7.2	8.3	8.7
Rated short circuit making capacity (I_{cm}) (kA) 690V	2.5	2.5	2.5	3.3	3.3
Rated short time withstand current (I_{cw}) (kA) 690V (1s)	1	1.1	1.6	1.7	2.3
Rated breaking capacity I_{cn} (A) AC23					
400V $\cos \phi$ 0.35	250	270	320	480	504
Electrical endurance (number of operations)	3000	3000	3000	3000	-
Mechanical endurance (number of operations)	50,000	50,000	50,000	50,000	-
Terminals mm ²	1.5 - 16	1.5 - 16	1.5 - 16	2.5 - 35	2.3 - 35
Max. thermal torque (Nm)	1.8	1.8	1.8	2.5	2.5