

LB PLUS busbar trunking systems

technical data

■ LB PLUS – Type B

Type		252	254	256	258	404	408	634
Number of live conductors		2	4	6	8	4	8	4
Casing overall dimensions	LxH [mm]	35 x 77	35 x 77	35 x 77	35 x 77	35 x 77	35 x 77	35 x 77
Rated current	I _n [A]	25	25	25	25	40	40	63
Operating voltage	U _e [V]	400	400	400	400	400	400	400
Insulation voltage	U _i [V]	500	500	500	500	500	500	500
Frequency	f [Hz]	50/60	50/60	50/60	50/60	50/60	50/60	50/60
Rated short-time current (0.1 s)	I _{cw} [kArms]	–	2.2	2.2	2.2	2.7	2.7	2.7
Peak current	I _{pk} [kA]	–	3.3	3.3	3.3	4.1	4.1	4.1
Single phase rated short-time current (0.1 s)	I _{cw} [kArms]	1.3	1.3	1.3	1.3	1.6	1.6	1.6
Single phase peak current	I _{pk} [kA]	2.0	2.0	2.0	2.0	2.4	2.4	2.4
Thermal limit	I ² t [A ² s x 10 ⁶]	0.174	0.484	0.484	0.484	0.729	0.729	0.729
20 °C phase resistance	R ₂₀ [mΩ/m]	4.761	4.761	4.761	4.761	3.190	3.190	1.595
Phase resistance at thermal conditions	R _t [mΩ/m]	5.656	5.656	5.656	5.656	3.802	3.802	1.901
Phase reactance (50Hz)	X [mΩ/m]	0.229	0.229	0.229	0.229	0.236	0.236	0.118
Phase impedance	Z [mΩ/m]	4.767	4.767	4.767	4.767	3.199	3.199	1.599
Resistance of the protective conductor ¹	R _{PE} [mΩ/m]	1.195	1.195	1.195	1.195	1.195	1.195	1.195
Reactance of the protective conductor ¹ (50Hz)	X _{PE} [mΩ/m]	0.274	0.274	0.274	0.274	0.274	0.274	0.274
Resistance of the fault loop	R _o [mΩ/m]	5.956	5.956	5.956	5.956	4.385	4.385	2.790
Reactance of the fault loop (50Hz)	X _o [mΩ/m]	0.503	0.503	0.503	0.503	0.510	0.510	0.392
Impedance of the fault loop	Z _o [mΩ/m]	5.977	5.977	5.977	5.977	4.415	4.415	2.817
Voltage drop with distributed load referred to V3f ³	ΔV 10 ⁻³ cosφ = 0.70 [V/m/A]	4.123 ²	3.570	3.570	3.570	2.830	2.451	1.225
	ΔV 10 ⁻³ cosφ = 0.75 [V/m/A]	4.393 ²	3.805	3.805	3.805	3.008	2.605	1.302
	ΔV 10 ⁻³ cosφ = 0.80 [V/m/A]	4.662 ²	4.038	4.038	4.038	3.183	2.757	1.378
	ΔV 10 ⁻³ cosφ = 0.85 [V/m/A]	4.928 ²	4.268	4.268	4.268	3.356	2.906	1.453
	ΔV 10 ⁻³ cosφ = 0.90 [V/m/A]	5.190 ²	4.495	4.495	4.495	3.525	3.052	1.526
	ΔV 10 ⁻³ cosφ = 0.95 [V/m/A]	5.445 ²	4.715	4.715	4.715	3.686	3.192	1.596
	ΔV 10 ⁻³ cosφ = 1.00 [V/m/A]	5.656 ²	4.898	4.898	4.898	3.802	3.293	1.646
Weight	p [kg/m]	1.80	1.83	2.02	2.02	1.98	2.33	2.33
Fire load	[kWh/m]	1.1	1.1	2.1	2.1	1.1	2.1	2.1
Protection index	IP	55	55	55	55	55	55	55
Degree of impact-resistance	IK	07	07	07	07	07	07	07
Joule effect losses at rated current	P [W/m]	10.6	10.6	10.6	10.6	18.2	18.2	22.6
Ambient temperature min-/MAX-	t [°C]	-5/+50	-5/+50	-5/+50	-5/+50	-5/+50	-5/+50	-5/+50

1 : Metal casing

2 : Single phase values with distributed load

3 : Three phase - see pg 12

Temperature rating schedule according to the room temperature

Room temperature [°C]	15	20	25	30	35	40	45	50	55	60
K1 Factor	1.15	1.12	1.08	1.05	1.025	1	0.975	0.95	0.93	0.89

Multiplier coefficient of rated current for room temperature values different from 40° C

Mechanical loads permitted table

The table shows the maximum weights (kg) that can be supported, both for concentrated, and distributed loads

LB PLUS – TYPE B	LB PLUS – TYPE A	Distance between suspension brackets	Concentrated load	Distributed load
		1.5	40	50 kg/m (75 kg) ⁴
		2.0	30	30 kg/m (60 kg) ⁴
		3.0	20	13 kg/m (39 kg) ⁴
		5.0	13	5 kg/m (25 kg) ⁴
		7.0	7	2 kg/m (14 kg) ⁴

4 : Distributed load total weight