

Swifts® extra heavy duty (Emerald)

cable ladder systems






EXTRA HEAVY DUTY (EMERALD)

	LADDER		COUPLERS		FITTINGS ⁽¹⁾					
	Widths (mm)	Emerald straight lengths (3 m) ⁽²⁾ F = finish	Coupler sets F = finish	Fitting to fitting coupler sets F = finish	Fitting to straight length fastener sets ⁽¹⁾ F = finish	Flat bends A = angle r = radius F = finish	Inside risers A = angle r = radius F = finish	Outside risers A = angle r = radius F = finish	Equal tees r = radius F = finish	Unequal tees B = branch r = radius F = finish
EXTRA HEAVY DUTY (EMERALD)	150	EL 150 F	EC F	EFC F	LF F M10P50	EFB 150 Ar F	EIR 150 Ar F	EOR 150 Ar F	ET 150 r R F	EUT 150 Br R F
	300	EL 300 F	EC F	EFC F	LF F M10P50	EFB 300 Ar F	EIR 300 Ar F	EOR 300 Ar F	ET 300 r R F	EUT 300 Br R F
	450	EL 450 F	EC F	EFC F	LF F M10P50	EFB 450 Ar F	EIR 450 Ar F	EOR 450 Ar F	ET 450 r R F	EUT 450 Br R F
	600	EL 600 F	EC F	EFC F	LF F M10P50	EFB 600 Ar F	EIR 600 Ar F	EOR 600 Ar F	ET 600 r R F	EUT 600 Br R F
	750	EL 750 F	EC F	EFC F	LF F M10P50	EFB 750 Ar F	EIR 750 Ar F	EOR 750 Ar F	ET 750 r R F	EUT 750 Br R F
	900	EL 900 F	EC F	EFC F	LF F M10P50	EFB 900 Ar F	EIR 900 Ar F	EOR 900 Ar F	ET 900 r R F	EUT 900 Br R F

(1) When connecting fittings to straight lengths, use fastener sets (not available in D finish) LFGM10P50, LFSM10P50, see p. 24



(2) 6 m lengths available on special request, contact us on +44 (0) 845 605 4333

FITTINGS⁽¹⁾


Branch piece F = finish	4 way crosspieces r = radius F = finish	Straight reducers K = reduced width F = finish	Offset reducers (left hand) K = reduced width F = finish	Offset reducers (right hand) K = reduced width F = finish
				
EB 150 300 R F	EX 150 r R F	-	-	-
EB 300 300 R F	EX 300 r R F	ESR 300 K F	ELR 300 K F	ERR 300 K F
EB 450 300 R F	EX 450 r R F	ESR 450 K F	ELR 450 K F	ERR 450 K F
EB 600 300 R F	EX 600 r R F	ESR 600 K F	ELR 600 K F	ERR 600 K F
EB 750 300 R F	EX 750 r R F	ESR 750 K F	ELR 750 K F	ERR 750 K F
EB 900 300 R F	EX 900 r R F	ESR 900 K F	ELR 900 K F	ERR 900 K F

Key : selecting extra heavy duty (Emerald) fittings
 Replace the letters shown in red with your choice from the following options :

- A = Angle (°) : 90, 60, 45 or 30
- B = Branch width (mm) : 150, 300, 450, 600, 750, 900
- F = Finish : G (hot dip galvanised after manufacture), D (deep galvanised), S (stainless steel)
- K = Narrowed width when using a reducer (mm) : 150, 300, 450, 600, 750
- r = Radius (mm) : 300, 600



Inside risers. See p. 18



Flat bends. See p. 18