

Salamandre® lighting trunking

selection chart

LIGHTING TRUNKING RANGE

| TRUNKING | | FITTINGS | | | | | | | | | | |
|---------------|-----------------|------------------|----------------|-----------------------------|-------------------|----------------------|-----------------------|-------------------|----------------------|-----------------------|---------------|---------------|
| Finish | Size (mm) | Lengths | Galvanised lid | White plastic standard lids | Top lid 90° bends | Inside lid 90° bends | Outside lid 90° bends | Top lid 45° bends | Inside lid 45° bends | Outside lid 45° bends | Top lid tees | |
| Galvanised | 50 x 50 | LT2 | LT2GC | LT2PC | LT2ASL | LT2BSL | LT2CSL | LT2AL | LT2BL | LT2CL | LT2AST | |
| Powder coated | 50 x 50 | WLT2 | WLT2GC | LT2PC | WLT2ASL | WLT2BSL | WLT2CSL | WLT2AL | WLT2BL | WLT2CL | WLT2AST | |
| FITTINGS | | | | ACCESSORIES | | | | | | | | |
| Finish | Inside lid tees | Outside lid tees | Crossovers | End caps | Flanges | Girder clamps | Stirrup hangers | Suspension units | Pull switch adaptors | Cable retainers | Klik adaptors | Long couplers |
| Galvanised | LT2BST | LT2CST | LT2ASX | LT2E | LT2F | LT2GCL | LT2H | LT2FS | LT2PSA | LT2CR | LT2KL | LT2C |
| Powder coated | WLT2BST | WLT2CST | WLT2ASX | WLT2E | WLT2F | WLT2GCL | WLT2H | LT2FS | LT2PSA | LT2CR | LT2KL | LT2C |