

## Salamandre® IP55 rated trunking

### IP55 rated trunking range

TRUNKING			FITTINGS							
Size (mm)	Lengths	Lids	Top lid 90° bends – gusset	Top lid 90° bends – square	Inside lid 90° bends – gusset	Inside lid 90° bends – square	Outside lid 90° bends – gusset	Outside lid 90° bends – square	Top lid 45° bends	
<b>1 COMPARTMENT</b>										
50 x 50	WSTIP22	WSTIP2LID	WSTIP22AGL	WSTIP22ASL	WSTIP22BGL	WSTIP22BSL	WSTIP22CGL	WSTIP22CSL	WSTIP22AL	
75 x 50	WSTIP32	WSTIP3LID	WSTIP32AGL	WSTIP32ASL	WSTIP32BGL	WSTIP32BSL	WSTIP32CGL	WSTIP32CSL	WSTIP32AL	
100 x 50	WSTIP42	WSTIP4LID	WSTIP42AGL	WSTIP42ASL	WSTIP42BGL	WSTIP42BSL	WSTIP42CGL	WSTIP42CSL	WSTIP42AL	
100 x 75	WSTIP43	WSTIP4LID	WSTIP43AGL	WSTIP43ASL	WSTIP43BGL	WSTIP43BSL	WSTIP43CGL	WSTIP43CSL	WSTIP43AL	
100 x 100	WSTIP44	WSTIP4LID	WSTIP44AGL	WSTIP44ASL	WSTIP44BGL	WSTIP44BSL	WSTIP44CGL	WSTIP44CSL	WSTIP44AL	
150 x 50	WSTIP62	WSTIP6LID	WSTIP62AGL	WSTIP62ASL	WSTIP62BGL	WSTIP62BSL	WSTIP62CGL	WSTIP62CSL	WSTIP62AL	
150 x 75	WSTIP63	WSTIP6LID	WSTIP63AGL	WSTIP63ASL	WSTIP63BGL	WSTIP63BSL	WSTIP63CGL	WSTIP63CSL	WSTIP63AL	
150 x 100	WSTIP64	WSTIP6LID	WSTIP64AGL	WSTIP64ASL	WSTIP64BGL	WSTIP64BSL	WSTIP64CGL	WSTIP64CSL	WSTIP64AL	
150 x 150	WSTIP66	WSTIP6LID	WSTIP66AGL	WSTIP66ASL	WSTIP66BGL	WSTIP66BSL	WSTIP66CGL	WSTIP66CSL	WSTIP66AL	
225 x 50	WSTIP92	WSTIP9LID	WSTIP92AGL	WSTIP92ASL	WSTIP92BGL	WSTIP92BSL	WSTIP92CGL	WSTIP92CSL	WSTIP92AL	
225 x 75	WSTIP93	WSTIP9LID	WSTIP93AGL	WSTIP93ASL	WSTIP93BGL	WSTIP93BSL	WSTIP93CGL	WSTIP93CSL	WSTIP93AL	
225 x 100	WSTIP94	WSTIP9LID	WSTIP94AGL	WSTIP94ASL	WSTIP94BGL	WSTIP94BSL	WSTIP94CGL	WSTIP94CSL	WSTIP94AL	
225 x 150	WSTIP96	WSTIP9LID	WSTIP96AGL	WSTIP96ASL	WSTIP96BGL	WSTIP96BSL	WSTIP96CGL	WSTIP96CSL	WSTIP96AL	
225 x 225	WSTIP99	WSTIP9LID	WSTIP99AGL	WSTIP99ASL	WSTIP99BGL	WSTIP99BSL	WSTIP99CGL	WSTIP99CSL	WSTIP99AL	

Trunking lengths and lids are sold separately

Each trunking length is supplied with one coupler and required TORX® head fixings and earth links

For all 2 compartment Cat. Nos. include 2C at the end of each product code shown above (except lids)

For all 3 compartment Cat. Nos. include 3C at the end of each product code shown above (except lids)

For 3 compartment products sizes 50 x 50 mm and 75 x 50 mm are not available

For all 2 and 3 compartment AGT (top lid tees – gusset), type A or type B cable exit configuration must be specified at time of order, (see p. 16)

	FITTINGS						ACCESSORIES			
	Inside lid 45° bends	Outside lid 45° bends	Top lid tees – gusset	Inside lid tees – gusset	Outside lid tees – gusset	Crossovers	Reducers	End caps	Flanges	Trunking couplers
WSTIP22BL	WSTIP22CL	WSTIP22AGT	WSTIP22BGT	WSTIP22CGT	WSTIP22AGX	–	WSTIP22E	WSTIP22F	WSTIP22C	
WSTIP32BL	WSTIP32CL	WSTIP32AGT	WSTIP32BGT	WSTIP32CGT	WSTIP32AGX	WSTIP32 Z R	WSTIP32E	WSTIP32F	WSTIP32C	
WSTIP42BL	WSTIP42CL	WSTIP42AGT	WSTIP42BGT	WSTIP42CGT	WSTIP42AGX	WSTIP42 Z R	WSTIP42E	WSTIP42F	WSTIP42C	
WSTIP43BL	WSTIP43CL	WSTIP43AGT	WSTIP43BGT	WSTIP43CGT	WSTIP43AGX	WSTIP43 Z R	WSTIP43E	WSTIP43F	WSTIP43C	
WSTIP44BL	WSTIP44CL	WSTIP44AGT	WSTIP44BGT	WSTIP44CGT	WSTIP44AGX	WSTIP44 Z R	WSTIP44E	WSTIP44F	WSTIP44C	
WSTIP62BL	WSTIP62CL	WSTIP62AGT	WSTIP62BGT	WSTIP62CGT	WSTIP62AGX	WSTIP62 Z R	WSTIP62E	WSTIP62F	WSTIP62C	
WSTIP63BL	WSTIP63CL	WSTIP63AGT	WSTIP63BGT	WSTIP63CGT	WSTIP63AGX	WSTIP63 Z R	WSTIP63E	WSTIP63F	WSTIP63C	
WSTIP64BL	WSTIP64CL	WSTIP64AGT	WSTIP64BGT	WSTIP64CGT	WSTIP64AGX	WSTIP64 Z R	WSTIP64E	WSTIP64F	WSTIP64C	
WSTIP66BL	WSTIP66CL	WSTIP66AGT	WSTIP66BGT	WSTIP66CGT	WSTIP66AGX	WSTIP66 Z R	WSTIP66E	WSTIP66F	WSTIP66C	
WSTIP92BL	WSTIP92CL	WSTIP92AGT	WSTIP92BGT	WSTIP92CGT	WSTIP92AGX	WSTIP92 Z R	WSTIP92E	WSTIP92F	WSTIP92C	
WSTIP93BL	WSTIP93CL	WSTIP93AGT	WSTIP93BGT	WSTIP93CGT	WSTIP93AGX	WSTIP93 Z R	WSTIP93E	WSTIP93F	WSTIP93C	
WSTIP94BL	WSTIP94CL	WSTIP94AGT	WSTIP94BGT	WSTIP94CGT	WSTIP94AGX	WSTIP94 Z R	WSTIP94E	WSTIP94F	WSTIP94C	
WSTIP96BL	WSTIP96CL	WSTIP96AGT	WSTIP96BGT	WSTIP96CGT	WSTIP96AGX	WSTIP96 Z R	WSTIP96E	WSTIP96F	WSTIP96C	
WSTIP99BL	WSTIP99CL	WSTIP99AGT	WSTIP99BGT	WSTIP99CGT	WSTIP99AGX	WSTIP99 Z R	WSTIP99E	WSTIP99F	WSTIP99C	

Key : **Z** = trunking size code

Replace **Z** with the relevant code (see p. 6)