

Salamandre® IP55 rated distribution trunking

order information

■ IP rated trunking

IP rated trunking is IP55 rated according to IEC 60529
For IP55 fittings see p. 8-9

■ Trunking size codes

All IP55 rated trunking product codes are pre-fixed with **WSTIP**

Size (mm) width x depth	IP55 trunking
50 x 50	22
75 x 50	32
75 x 75	33
100 x 50	42
100 x 75	43
100 x 100	44
150 x 50	62
150 x 75	63
150 x 100	64
150 x 150	66
225 x 50	92
225 x 75	93
225 x 100	94
225 x 150	96
225 x 225	99

In the Cat. Nos. shown on p. 4-5,
replace **Z** with the relevant
standard trunking size code

■ Finishes

IP55 rated distribution trunking is made from steel with a CPC (clear powder coating)

■ Compartment options

WSTIP range of trunking is available in 1, 2 and 3 compartment options
See selection chart (p. 4-5) for options

Trunking and fittings are supplied with equal compartments as standard. For unequal compartments, details must be supplied at the time of order

3 compartment is available in width code 3 and above

Distribution trunking lengths

For 1 compartment trunking there is no need to change the Cat. No. Example : WSTIP44

For 2 compartment trunking, add **2C** to the end of the Cat. No. Example : WSTIP44**2C**

For 3 compartment trunking, add **3C** to the end of the Cat. No. Example : WSTIP44**3C**

Distribution trunking fittings

For 1 compartment trunking there is no need to change the Cat. No. Example : WSTIP44AGL

For 2 compartment trunking, add **2C** to the end of the Cat. No. Example : WSTIP44AGL**2C**

For 3 compartment trunking, add **3C** to the end of the Cat. No. Example : WSTIP44AGL**3C**

Multi-compartment tees – Top lid tees – gusset

2 and 3 compartment AGT (top lid tees – gusset) must be suffixed with either **A** or **B** to denote the cable exit configuration on the tee branch, Cat. No. Example : WSTIP44AGT**3CA**

Please refer to p. 16 to determine type **A** or type **B** for the cable exit configuration

■ Lid fixings

Standard WSTIP lids are supplied with TORX®¹ screw fixings

■ Fittings

The chart below details each element required to correctly order a fitting

E.g. **WSTIP33AGX2C** = 75 x 75 top lid gusset crossover 2 compartment

Range	Width	Height	Cover position	Gusset / Square	Function	Compartment
WSTIP	2 = 50 mm	2 = 50 mm	A = Top B = Internal C = External	G = Gusset S = Square	L = Bend T = Tee X = Crossover	2C = 2 Compartment 3C = 3 Compartment
	3 = 75 mm	3 = 75 mm				
	4 = 100 mm	4 = 100 mm				
	6 = 150 mm	6 = 150 mm				
	9 = 225 mm	9 = 225 mm				

1 : TORX® is a registered trademark of Acument Intellectual Properties LLC

All dimensions (mm) are nominal