

Fire rated by design / Self-sealing system

- No firestop handling required for cable changes
- Fire safety compliant all the time


Product Description

- Cable management solution
- Supports easy installation, moves, additions and changes
- Cable friendly design, no sharp edges
- Up to 100% visual cable loading
- Approved for all types of cables
- Mechanical system for easy installation
- For fire and smoke barriers

Applications

- For all types of cables (up to Ø21 mm)
- Rigid walls, flexible walls and rigid floors

Ordering Information



CM250018






1.2



1

EZ-Path® is the only fire-rated cable management system with no firestop handling



Please refer to the document "Cable Capacity Series 33"

Technical Data

Fire Resistance (EN 1366-3)	up to 4 Hours	Shell Composition	1.5 mm thick galv. steel
Classification (EN 13501-2)	up to EI120 / E240	Expansion begins	177 °C
Reaction to Fire (EN 13501-1)	Class E	Volume Expansion	15x
Sound Insulation (ASTM E90)	STC 50 (relates to specific construction)	In-Service Temperature	Not to exceed 49°C
Air Leakage (EN1026 and UL1479)	0.70 m3/h, 0% cable 1.68 m3/h, 100% cables	Storage Temperature	Not to exceed 49°C
Durability and Serviceability	Type Y2	Shelf Life	No limit
Halogen free in accordance to IEC 61249-2-21		VOC Content ASTM D3960 or EPA Method 24	None

Approvals

ETA - 18/0412



0843



EZ-Path® is the only fire-rated cable management system with no firestop handling


No plate required
CM250018 only

Rigid walls


All types of cables
outside diameter $\leq \varnothing 21\text{mm}$

up to EI 90

Can be used for existing cables



One or two CM250018 (EZD33T)




CM250018 + Plate Kit

Flexible and Rigid walls / Rigid floors

All types of cables
outside diameter $\leq \varnothing 21\text{mm}$

up to EI 120

Single CM250018 (EZD33T)



up to seven CM250018 (EZD33T)






Plate kits to be used in association with CM250018 (EZD33T)




Please refer to ETA 18/0412 , the Application Data Sheets and the Installation Data Sheets

EZ-Path® Fire Rated Pathway Series 33

CM250018
EZD33T

EZ-Path device

weight : 1.2 kg







Extension device (for thicker barrier)

CM250078
EZD33E

Extension device


weight : 0.73 kg



Wall plate kits : All types of cables with OD ≤ Ø 21


CM250240
EZP133CWT

Single wall plate
weight : 0.4 kg




CM250140
EZP433WT

Four gang wall plate
weight : 0.9 kg




CM250120
EZP233WT

Two gang wall plate
weight : 0.5 kg




CM250170
EZP733WT

Seven gang wall plate
weight : 1.5 kg



CM250130
EZP333WT

Three gang wall plate
weight : 0.6 kg



Please contact the local representative for the availability of the plate kit CM250170.

Floor plate kit : All types of cables with OD ≤ Ø 21

CM250220
EZP133KT

Single floor plate
weight : 0.4 kg




Plate kits to be used in association with CM250018 (EZD33T)

Please refer to ETA 18/0412 , the Application Data Sheets and the Installation Data Sheets