

# Steel floor-standing enclosures

## Accessories

### Panels

SF



SF



SF



Characteristics		Side door	External fixing	Internal fixing
		Door for the side of the enclosure, replaces the side panel. Installation directly on the structure of the enclosure, opening 120°. Lock with handle and 5-mm double-bar insert. 4 locking points. Reinforcement frame, cut-out with a pitch of 25 mm. Opening to right or left.	Set of 2 side panels fixed from the outside of the enclosure.	Set of 2 side panels fixed from the enclosure, preventing access by unauthorized persons. Very useful in public spaces.
Material		Steel	Steel	Steel
Finish		Painted with epoxy-polyester resin	Painted with epoxy-polyester resin	Painted with epoxy-polyester resin
Colour		RAL 7035 grey	RAL 7035 grey	RAL 7035 grey
Supply		One side door, four hinges, four catches and handle lock	2 side panels and fixing elements	2 side panels, with sealing gasket and bag of accessories
Height (mm)	Depth (mm)	References		
1200	400	-	NSY2SP124	-
	500	-	NSY2SP125	NSY2SPI126
	600	NSYSFD126	NSY2SP126	-
	800	NSYSFD128	NSY2SP128	-
1400	400	-	NSY2SP144	-
	500	-	NSY2SP145	-
	600	NSYSFD146	NSY2SP146	-
	800	NSYSFD148	NSY2SP148	-
1600	400	-	NSY2SP164	-
	500	-	NSY2SP165	-
	600	NSYSFD166	NSY2SP166	-
	800	NSYSFD168	NSY2SP168	-
1800	400	NSYSFD184	NSY2SP184	-
	500	NSYSFD185	NSY2SP185	NSY2SPI185
	600	NSYSFD186	NSY2SP186	NSY2SPI186
	800	NSYSFD188	NSY2SP188	NSY2SPI188
	1000	-	-	-
2000	400	NSYSFD204	NSY2SP204	NSY2SPI204
	500	NSYSFD205	NSY2SP205	NSY2SPI205
	600	NSYSFD206	NSY2SP206	NSY2SPI206
	800	NSYSFD208	NSY2SP208	NSY2SPI208
	1000	-	-	-
	1200	-	-	-
2200	400	NSYSFD224	NSY2SP224	-
	500	NSYSFD225	NSY2SP225	-
	600	NSYSFD226	NSY2SP226	NSY2SPI226
	800	NSYSFD228	NSY2SP228	NSY2SPI228
	1000	-	-	-