

# Polyester floor-standing enclosures

## Specific accessories

### Installation accessories


PB501385-10  
PB501385-29




PB500187-26



DB300659-38



Characteristics		Support plate		M8 inserts	Intermediate support in the 2-door enclosures
		<ul style="list-style-type: none"> <li>Designed to support assorted equipment or simply to install a separation.</li> <li>In the 2-door enclosures, the installation of the plate or the uprights requires the prior installation of an intermediate support, ref. <b>NSYSBPLA</b>, presented beside.</li> </ul>		To be placed in the bosses moulded on the doors, uprights, rear panels and bottom and top parts, for fixing accessories and assorted devices.	Required accessory for installing support plates, ref. <b>NSYBANPLA●●●</b> or uprights, ref. <b>NSYSPLA●●●</b> in the 2-door enclosures.
Material		Galvanised-steel		-	-
Installation		<ul style="list-style-type: none"> <li>It is installed directly on the bottom part of the enclosure</li> <li>For the installation of one or several support plates, use 2 sets of 2 uprights suitable for the height (to be ordered separately). These uprights offer the option of adjusting the height with a step of 50 mm</li> </ul>		-	-
Supply		Delivered with the fixings required for installation		References by unit. Order by multiples of 8 units (8, 16, 24, etc.)	-
For enclosure (mm)		Upright			
Height	Depth	No. of adjustments	References	Reference	Reference
750	320	2	2 x <b>NSYSPLA75</b>	<b>NSYTEX8</b>	<b>NSYSBPLA</b>
	420				
1000	320	3	2 x <b>NSYSPLA100</b>		
	420				
1250	320	4	2 x <b>NSYSPLA125</b>		
	420				
1500	-	5	2 x <b>NSYSPLA150</b>		
For enclosure (mm)		Plate			
Depth (C)	Width (B)	Max. load	References		
320	500	60 kg	<b>NSYBANPLA53</b>		
	750	60 kg	<b>NSYBANPLA73</b>		
420	500	50 kg	<b>NSYBANPLA54</b>		
	750	50 kg	<b>NSYBANPLA74</b>		
620	500	50 kg	<b>NSYBANPLA56</b>		
	750	50 kg	<b>NSYBANPLA76</b>		
 <p>PB502923-30</p> <p><b>Upright</b></p> <p>DB300659-23</p> <p>(1) (2) (3) (4)</p> <p><b>Plate</b></p> <p>DB300657-27</p> <p>C-80</p> <p>27 12 25 18</p> <p>B-42</p>					

(1) **NSYSPLA75** ; (2) **NSYSPLA100** ; (3) **NSYSPLA125** ; (4) **NSYSPLA150**.