


# Cable management

## Cable holding

CRN

S3D

S3X



Characteristics	Plastic cable support			Door cable-guide cross-rails for wall-mounting enclosures	
	It clips or screws onto 35 mm symmetric rails or a C-shaped rail.			<ul style="list-style-type: none"> <li>■ They are installed on wall-mounting enclosures with heights from 400 mm for Spacial S3D and 500 mm for Spacial S3X.</li> <li>■ They make it easy to equip the inside of the door.</li> <li>■ Installation cable ties, see page 258.</li> </ul>	
Fixing	Quick and easy fixing of cables using cable ties			<ul style="list-style-type: none"> <li>■ They are fixed to the door reinforcement frame by 2 self-tapping screws. The angle can be directed towards the body of the enclosure or towards the door</li> </ul>	
Supply	10 units. Reference by unit. Order by multiples of 10 (10, 20, 30...)			2 cable-guide cross-rails and fixing elements	
Dimensions (mm)	Support dimensions (mm)	Maximum no. of cables	References	Door dimensions (mm)	References
	Width			Width	
	75	5	NSYSCCDINLG75	400	NSYTFPCR4
	140	9	NSYSCCDINLG140	500	NSYTFPCR5
				600	NSYTFPCR6
				800	NSYTFPCR8
				1000	NSYTFPCR10
	<p>DB300418EN-59</p>			<p>DB300420-25</p>	