SL

## making connections beautifully

Totige Hartland Grid-IT Gloss White 1 Gang Grid Fix Aperture Plate with Grid  Item Image  Wiring  Dimensions  HartLANG Top Single plate with 1 of Both 1 of	Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio			
Primary Range GRID-IT Insert Type 1 Gang Grid Fix Aperture Plate with Grid Plate Finish Hartland GRID-IT Gloss White Insert Colour No Insert Colour EAN13 Barcode 5051164709013 Dimensions (Nominal) Single: Height = 88.0mm Width = 88.0mm Depth = 5.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = 49.2mm Minimum Wall Box Depth As Per Insert Switched Poles N/A IP Rating NA Contact Gap Minimum EAN14 Face plate must be earthed		<u>701GP</u>		
Primary Range GRID-IT Insert Type 1 Gang Grid Fix Aperture Plate with Grid Plate Finish Hartland GRID-IT Gloss White Insert Colour No Insert Colour EAN13 Barcode 5561164709013 Dimensions (Nominal) Single: Height = 88.0mm Width = 88.0mm Depth = 5.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = 49.2mm Minimum Wall Box Depth As Per Insert Switched Poles N/A IP Rating N/A Contact Gap Minimum East Open N/A IP Rating N/A Contact Gap Minimum Mal Face Poles I Imm2 Froduct Class 1 Face plate must be earthed	Hartland Grid	-IT Gloss White 1 Gang Grid Fix Aperture P	late with Grid	
Primary Range GRID-IT Insert Type 1 Gang Grid Fix Aperture Plate with Grid Plate Finish Hartland GRID-IT Gloss White Insert Colour EAN13 Barcode Sos1164709013 Dimensions (Nominal) Single: Height = 88.0mm Width = 88.0mm Depth = 5.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = 49.2mm Minimum Wall Box Depth As Per Insert Switched Poles N/A IP Rating N/A Centact Gap Minimum N/A Face plate must be earthed	Transaction of State Village Transportation late With State			
Primary Range   GRID-IT	Item Image	Wiring	Dimensions	
Insert Type  1 Gang Grid Fix Aperture Plate with Grid  Plate Finish  Hartland GRID-IT Gloss White  Insert Colour  EAN13 Barcode  5051164709013  Dimensions (Nominal)  Single: Height = 88.0mm Width = 88.0mm Depth = 5.0mm  Fixing Hole Centres  Box Fixing = 60.3mm Grid Fixing = 49.2mm  Minimum Wall Box Depth  As Per Insert  Switched Poles  N/A  IP Rating  N/A  Contact Gap Minimum  N/A  Earth Terminal Capacity 1  Product Class 1  Face plate must be earthed			Single plate with 1 x GRID-IT cutout	
Insert Colour	, ,			
EAN13 Barcode         5051164709013           Dimensions (Nominal)         Single: Height = 88.0mm Width = 88.0mm Depth = 5.0mm           Fixing Hole Centres         Box Fixing = 60.3mm Grid Fixing = 49.2mm           Minimum Wall Box Depth         As Per Insert           Switched Poles         N/A           IP Rating         N/A           Contact Gap Minimum         N/A           Earth Terminal Capacity 1         11mm2           Product Class 1         Face plate must be earthed	Plate Finish	Hartland GRID-IT Gloss White		
Dimensions (Nominal)  Single: Height = 88.0mm Width = 88.0mm Depth = 5.0mm  Fixing Hole Centres  Box Fixing = 60.3mm Grid Fixing = 49.2mm  Minimum Wall Box Depth  As Per Insert  Switched Poles  N/A  IP Rating  N/A  Contact Gap Minimum  N/A  Earth Terminal Capacity 1  Product Class 1  Face plate must be earthed	Insert Colour	No Insert Colour		
Fixing Hole Centres         Box Fixing = 60.3mm	EAN13 Barcode	5051164709013		
Minimum Wall Box Depth As Per Insert  Switched Poles N/A  IP Rating N/A  Contact Gap Minimum N/A  Earth Terminal Capacity 1 11mm2  Product Class 1 Face plate must be earthed	Dimensions (Nominal)	Single: Height = 88.0mm Width = 88.0mm Depth = 5.0mm		
Switched Poles         N/A           IP Rating         N/A           Contact Gap Minimum         N/A           Earth Terminal Capacity 1         11mm2           Product Class 1         Face plate must be earthed	Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = 49.2mm		
IP Rating N/A  Contact Gap Minimum N/A  Earth Terminal Capacity 1 11mm2  Product Class 1 Face plate must be earthed	Minimum Wall Box Depth	As Per Insert		
Contact Gap Minimum N/A  Earth Terminal Capacity 1 11mm2  Product Class 1 Face plate must be earthed	Switched Poles	N/A		
Earth Terminal Capacity 1 11mm2 Product Class 1 Face plate must be earthed	IP Rating	N/A		
Product Class 1 Face plate must be earthed	Contact Gap Minimum	N/A		
	Earth Terminal Capacity 1	11mm2		
Recommended Location Internal Use Only	Product Class 1	Face plate must be earthed		
	Recommended Location	Internal Use Only		
Maximum Installation Altitude 2000m	Maximum Installation Altitude	2000m		
Additional Notes See GRID-IT for a full range of inserts. Plates must be Earthed via the Earth Tag.	Additional Notes	See GRID-IT for a full range of inserts. Plates must be Earthed via the Earth Tag.		
All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designs and dimensions without prior notice.	European standard and the product information is	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	Therefore, we reserve the right to alter designs	
the limitations of reproduction and printing guarantee an exact colour match and shadings of process and are not binding. guarantee an exact colour match and shadings of of certain finishes.	the limitations of reproduction and printing process and are not binding.	guarantee an exact colour match and shadings of of certain finishes.	Correct as at 15 October 2018 09:51 AM E&OE	

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84









