

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

70C1X40

Insert Type 1 gar Plate Finish Hartt	Hartland CFX Gloss White 1x400W Resistive Leading Edge Push On-Off Rotary 2 Way Switching Dimmer Gloss White		
Insert Type 1 gar Plate Finish Hartt	Wiring	Dimensions	
Insert Type 1 gar Plate Finish Hartt	Dimmer Wiring Lee Nordral Learn Loop In Loop Cut. Two Way Switching Learn Large Loop In Loop Cut. Two Way Switching Loop Cut. Two Way Switching Loop In Loop Cut. Two Way Switching Loop Cu	Hemilton HARTLAND CFX 1X40 Resistive Leading Edge Push On-Off Rotary 2 Way Switching Dimmer	
Plate Finish Hartl	and CFX		
	1 gang 400W Resistive Leading Edge Push On-Off Rotary 2 Way Switching Dimmer		
	Hartland CFX Gloss White		
Insert Colour Gloss	Gloss White		
EAN13 Barcode 5017	5017504008390		
Dimensions (Nominal) Singl	Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm		
Fixing Hole Centres Box I	Box Fixing = 60.3mm Grid Fixing = CFX Clips		
Minimum Wall Box Depth 35mr	35mm		
Wattage 400V	400W		
Switched Poles Singl	Single		
Current Rating 1.66	1.66 Amp		
Voltage 220/2	220/250V AC		
Maximum Load 400V	400W resistive Min Load		
Mains Frequency 50Hz	50Hz		
IP Rating IP2X	IP2XD		
Contact Gap Minimum N/A	N/A		
Terminal Capacity 1 2 x 1	2 x 1mm2		
Terminal Capacity 2 2 x 1	2 x 1.5mm2		
Earth Terminal Capacity 1 5 x 1	5 x 1mm2		
Earth Terminal Capacity 2 4 x 1	4 x 1.5mm2		
Earth Terminal Capacity 3 3 x 2	3 x 2.5mm2		
Earth Terminal Capacity 4 1 x 4	1 x 4mm2 Multi-strand		
Earth Terminal Capacity 5 1 x 6	1 x 6mm2		
Product Class 1 Face	Face plate must be earthed		
Ambient Operating Temperature -5° to	-5° to +40°C		
Recommended Location Intern	Internal Use Only		
Maximum Installation Altitude 2000	2000m		
Standard/Approval BS E	BS EN 60669-2-1		
Additional Notes shou	Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltagehalogen lamps- dimmers should be de-rated by 25%. When dimming LED lamps de-rated by 75% - please contact our Technical for compatibility.		
Patents and Trademarks Hartle	CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445		
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.	
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 16 October 2018 12:36 PM E&OE	

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84















Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio